

Product datasheet

Specifications



servo motor BCH16, Lexium 16D,
80mm, shaft 19mm, 750W, Heavy
inertia, 3000rpm, 23bit

BCH16HF07332A5C2

Main

Range Compatibility	Easy Lexium 16
Product Or Component Type	Servo motor
Device Short Name	BCH16

Complementary

Maximum Mechanical Speed	5000 rpm
[Us] Rated Supply Voltage	220 V
Network Number Of Phases	3 phases
Continuous Stall Current	4.3 A
Continuous Stall Torque	2.39 N.m for LXM16D at 7.81 A, 220 V, single phase
Continuous Power	750 W
Peak Stall Torque	7.16 N.m for LXM16D at 7.81 A, 220 V, single phase
Nominal Output Power	750 W for LXM16D at 7.81 A, 220 V, single phase
Nominal Torque	2.39 N.m for LXM16D at 7.81 A, 220 V, single phase
Nominal Speed	3000 rpm for LXM16D at 7.81 A, 220 V, single phase
Maximum Current Irms	15.3 A for LXM16D at 0.75 kW, 220 V
Maximum Permanent Current	14 A
Product Compatibility	LXM16D motion servo motors motor at 0.75 kW, 220 V, single phase
Shaft End	Parallel key
Second Shaft	Without second shaft end
Shaft Diameter	19 mm
Shaft Length	22 mm
Key Width	6 mm
Feedback Type	23 bit hight resolution encoder
Holding Brake	Without
Holding Torque	3.0 N.m
Mounting Support	Asian standard flange
Motor Flange Size	80 mm
Electrical Connection	Free lead
Torque Constant	0.56 N.m/A at 20 °C
Back Emf Constant	37.3 V/krpm at 20 °C

Rotor Inertia	1.51 kg.cm ²
Stator Resistance	1.51 Ohm at 20 °C
Stator Inductance	9.2 mH at 20 °C
Stator Electrical Time Constant	6.09 ms at 20 °C
Maximum Radial Force Fr	221.48 N at 3000 rpm
Maximum Axial Force Fa	61.74 N
Type Of Cooling	Natural convection
Length	137 mm
Centring Collar Diameter	70 mm
Centring Collar Depth	3 mm
Number Of Mounting Holes	4
Mounting Holes Diameter	6.5 mm
Circle Diameter Of The Mounting Holes	90 mm
Distance Shaft Shoulder-Flange	36 mm
Width	80 mm
Height	93 mm
Depth	137 mm
Net Weight	2.7 kg

Environment

Ip Degree Of Protection	IP65 IM B5, IM V1 IP65 IM V3
Ambient Air Temperature For Operation	0...40 °C

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	13.5 cm
Package 1 Width	17.0 cm
Package 1 Length	27.5 cm
Package 1 Weight	2.85 kg
Unit Type Of Package 2	S04
Number Of Units In Package 2	8
Package 2 Height	30.0 cm
Package 2 Width	40.0 cm
Package 2 Length	60.0 cm
Package 2 Weight	23.56 kg

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Reach Free Of Svhc

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)
