

# TeSys LE - enclosed DOL starter - 9 A - 230 V AC coil

LE1D09P7

| ١ | / | a | ı | r | 1 |
|---|---|---|---|---|---|
|   |   |   |   |   |   |

| Range                     | TeSys  |
|---------------------------|--|
| Product name              | TeSys LE   |
| Device short name         | LE1D   |
| Product or component type | Enclosed DOL starter                                   |
| Device application        | Standard   |
| Utilisation category      | AC-3   |
| Device composition        | Thermal overload relay ordered separately<br>Contactor |
| Control type              | Push-button start green I Push-button stop/reset red O |

### Complementary

| Motor power kW                              | 4 kW at 380/400 V AC 50/60 Hz<br>4 kW at 415 V AC 50/60 Hz<br>4 kW at 440 V AC 50/60 Hz<br>2.2 kW at 220/230 V AC 50/60 Hz<br>5.5 kW at 500 V AC 50/60 Hz<br>5.5 kW at 660/690 V AC 50/60 Hz |
|---|--|
| [Ith] Conventional free air thermal current | 9 A  |
| [Uc] control circuit voltage                | 230 V AC 50/60 Hz  |
| Cable entry number                          | 2 ISO20 top<br>2 ISO20 bottom<br>2 Pg 13 bottom<br>2 Pg 16 bottom  |
| Width                                       | 88 mm  |
| Height                                      | 166 mm   |
| Depth                                       | 128.5 mm   |
| Net weight                                  | 0.92 kg  |

#### **Environment**

| Material                | Polycarbonate                |
|-------------------------|------------------------------|
| IP degree of protection | IP65 conforming to IEC 60529 |
| IK degree of protection | IK07 conforming to IEC 60529 |
| Standards               | IEC 60947-4-1                |

| Ambient air temperature for operation | -540 °C   |
|---------------------------------------|---|
| Environmental characteristic          | Standard environment  |
| Product certifications                | UKCA  |
| Packing Units                         |   |
| Unit Type of Package 1                | PCE   |
| Number of Units in Package 1          | 1   |
| Package 1 Height                      | 15.0 cm   |
| Package 1 Width                       | 17.2 cm   |
| Package 1 Length                      | 20.6 cm   |
| Package 1 Weight                      | 888.0 g   |
| Unit Type of Package 2                | P06   |
| Number of Units in Package 2          | 30  |
| Package 2 Height                      | 80.0 cm   |
| Package 2 Width                       | 80.0 cm   |
| Package 2 Length                      | 60.0 cm   |
| Package 2 Weight                      | 39.64 kg  |
| Offer Sustainability                  |   |
| Sustainable offer status              | Green Premium product   |
| REACh Regulation                      | REACh Declaration   |
| REACh free of SVHC                    | Yes   |
| EU RoHS Directive                     | Compliant EU RoHS Declaration   |
| Toxic heavy metal free                | Yes   |
| Mercury free                          | Yes   |
| China RoHS Regulation                 | China RoHS declaration  |
| RoHS exemption information            | Yes   |
| Environmental Disclosure              | Product Environmental Profile   |
| Circularity Profile                   | End of Life Information   |
| WEEE                                  | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins   |
| California proposition 65             | WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov |

# **Contractual warranty**

Warranty 18 months

## Recommended replacement(s)