

MAXIBLOCK CABLE GLAND, IN POLYAMIDE PA6.6, PG PITCH, IP68


Features

TECHNICAL INFORMATION

Minimum operating temperature	-20 °C
Maximum operating temperature	90 °C
Ingress Protection	IP68
Counter nut	No
Dust-proof disc	No
Internal washers	No
EMC	No
Markings found	factory mark; thread type; certification logos
Reference standard	CEI EN 62444; DIN 40430
Conditions of use	static and dynamic, indoor and outdoor
Self-extinguishing fire class according to UL 94	V2

LOGISTIC


Type of packaging	; box
Customs code	39269097

MATERIAL COMPOSITION AND TREATMENTS

Entry bush material	Poliammide PA6.6
Inner seal material	Neoprene
Body material	Poliammide PA6.6
Halogen free	No

CLASSIFICATION AND DATA ORDERING

ETIM Class 7	Cable gland [EC000441]
Manufactured in	Italy



1900 PG

tipo	P	External seal	Colour	Outer seal material	Tightening torque [nm]	Range of cable housing diameter [mm]	B1 [mm]	B2 [mm]	C [mm]	L [mm]	Fixing hole diameter [mm]	Width [mm]	Gross weight [g]	Unit in standard packaging [pce]	Minimum order quantity [pce]
1900.07	Pg7	No	Grey RAL 7035		2.5	3.5 ÷ 7	15	15	8	18 ÷ 22	12.7	16.5	3,660	100	100
1900.07N	Pg7	No	Black RAL 9005		2.5	3.5 ÷ 7	15	15	8	18 ÷ 22	12.7	16.5	3,620	100	100
1900.07G	Pg7	No	Dark grey RAL 7001		2.5	3.5 ÷ 7	15	15	8	18 ÷ 22	12.7	16.5	3,640	100	100
1900.09	Pg9	No	Grey RAL 7035		3.75	5 ÷ 8	19	19	8	22 ÷ 26	15.5	21	6,580	100	100
1900.09N	Pg9	No	Black RAL 9005		3.75	5 ÷ 8	19	19	8	22 ÷ 26	15.5	21	6,640	100	100
1900.09G	Pg9	No	Dark grey RAL 7001		3.75	5 ÷ 8	19	19	8	22 ÷ 26	15.5	21	6,520	100	100
1900.11	Pg11	No	Grey RAL 7035		3.75	5 ÷ 10	22	22	8	23 ÷ 28	18.8	24.5	8,880	100	100
1900.11N	Pg11	No	Black RAL 9005		3.75	5 ÷ 10	22	22	8	23 ÷ 28	18.8	24.5	8,740	100	100
1900.11G	Pg11	No	Dark grey RAL 7001		3.75	5 ÷ 10	22	22	8	23 ÷ 28	18.8	24.5	8,030	100	100
1900.13	Pg13,5	No	Grey RAL 7035		5	7 ÷ 12	24	24	9	24 ÷ 29	20.5	27	10,650	100	100
1900.13N	Pg13,5	No	Black RAL 9005		5	7 ÷ 12	24	24	9	24 ÷ 29	20.5	27	10,820	100	100
1900.13G	Pg13,5	No	Dark grey RAL 7001		5	7 ÷ 12	24	24	9	24 ÷ 29	20.5	27	10,880	100	100
1900.16	Pg16	No	Grey RAL 7035		5	10 ÷ 14	27	27	10	26 ÷ 31	22.6	29	14,000	50	50
1900.16N	Pg16	No	Black RAL 9005		5	10 ÷ 14	27	27	10	26 ÷ 31	22.6	29	13,720	50	50
1900.16G	Pg16	No	Dark grey RAL 7001		5	10 ÷ 14	27	27	10	26 ÷ 31	22.6	29	13,960	50	50
1900.21	Pg21	Yes	Grey RAL 7035	Neoprene	7.5	13 ÷ 18	33	33	12	30 ÷ 35	28.5	36.5	22,160	50	50
1900.21N	Pg21	Yes	Black RAL 9005		7.5	13 ÷ 18	33	33	12	30 ÷ 35	28.5	36.5	21,880	50	50
1900.21G	Pg21	Yes	Dark grey RAL 7001	Neoprene	7.5	13 ÷ 18	33	33	12	30 ÷ 35	28.5	36.5	22,120	50	50

tipo	P	External seal	Colour	Outer seal material	Tightening torque [nm]	Range of cable housing diameter [mm]	B1 [mm]	B2 [mm]	C [mm]	L [mm]	Fixing hole diameter [mm]	Width [mm]	Gross weight [g]	Unit in standard packaging [pce]	Minimum order quantity [pce]
1900.29	Pg29	Yes	Grey RAL 7035	Neoprene	8	18 ÷ 25	42	42	12	33 ÷ 39	37.2	46	37,200	25	25
1900.29N	Pg29	Yes	Black RAL 9005	Neoprene	8	18 ÷ 25	42	42	12	33 ÷ 39	37.2	46	37,120	25	25
1900.29G	Pg29	Yes	Dark grey RAL 7001	Neoprene	8	18 ÷ 25	42	42	12	33 ÷ 39	37.2	46	37,600	25	25
1900.36	Pg36	Yes	Grey RAL 7035	Neoprene	10	20 ÷ 32	53	53	14	42 ÷ 49	47.2	58.5	79,400	10	10
1900.36N	Pg36	Yes	Black RAL 9005	Neoprene	10	20 ÷ 32	53	53	14	42 ÷ 49	47.2	58.5	80,000	10	10
1900.36G	Pg36	Yes	Dark grey RAL 7001	Neoprene	10	20 ÷ 32	53	53	14	42 ÷ 49	47.2	58.5	79,000	10	10
1900.42	Pg42	Yes	Grey RAL 7035	Neoprene	10	28 ÷ 38	60	60	14	42 ÷ 50	54.2	67	100,000	5	5
1900.42N	Pg42	Yes	Black RAL 9005	Neoprene	10	28 ÷ 38	60	60	14	42 ÷ 50	54.2	67	100,800	5	5
1900.42G	Pg42	Yes	Dark grey RAL 7001	Neoprene	10	28 ÷ 38	60	60	14	42 ÷ 50	54.2	67	101,600	5	5
1900.48	Pg48	Yes	Grey RAL 7035	Neoprene	15	34 ÷ 45	66	66	15	45 ÷ 55	60	72	112,800	5	5
1900.48N	Pg48	Yes	Black RAL 9005	Neoprene	15	34 ÷ 45	66	66	15	45 ÷ 55	60	72	110,000	5	5
1900.48G	Pg48	Yes	Dark grey RAL 7001	Neoprene	15	34 ÷ 45	66	66	15	45 ÷ 55	60	72	116,600	5	5