

Product data sheet

Specifications



Electronic thermal overload relay, TeSys Giga, 28-115 A, class 5E-30E, push-in control connection

LR9G115

Product availability : Stock - Normally stocked in distribution facility

Price* : 660.00 USD

Main

Range	TeSys
Product name	TeSys LRG
Product or Component Type	Electronic thermal overload relay
Device short name	LR9G
Relay application	Motor protection
Network type	AC
Thermal overload class	Class 5E...30E IEC 60947-4-1
Thermal protection adjustment range	28...115 A

Complementary

Network Frequency	30...60 Hz 100 Hz
Overvoltage category	III
Tripping threshold	1.125 +/- 0.07 In IEC 60947-4-1
Protection type	Ground fault protection 0...1 s - alarm circuit IEC 60947-4-1 Ground fault protection 0...1 s - alarm circuit UL 60947-4-1 Phase loss 0...4 s - alarm circuit Phase imbalance 0...5 s - alarm circuit IEC 60947-4-1 Phase imbalance 0...5 s - alarm circuit UL 60947-4-1
Local signalling	LED Trip indicator
Contacts type and composition	1 NO + 1 NC
[Ith] conventional free air thermal current	5 A
[Uc] control circuit voltage	24...500 V AC 50/60 Hz 24...250 V DC
[Ue] rated operational voltage	1000 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
Reset	Automatic reset Manual
Mechanical durability	7000 cycles
Surge withstand	4 kV

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Electromagnetic compatibility	EMC immunity IEC 60947-4-1 Emission test criteria A IEC 60947-4-1 Immunity to radiated radio-electrical interference 20 V/m EN/IEC 61000-4-3 Voltage dips and interruptions immunity test SEMI F47
Connections - terminals	Power circuit bar 25 x 6 mm Power circuit lugs-ring terminals 1 0.29 in ² (185 mm ²) Control circuit push-in 1 0.00...0.00 in ² (0.2...2.5 mm ²) solid stranded without cable end Control circuit push-in 1 0.00...0.00 in ² (0.25...2.5 mm ²) flexible with cable end Control circuit push-in 2 0.00...0.00 in ² (0.5...1.0 mm ²) with cable end
Tightening torque	18 N.m
Mounting support	Direct on contactor Plate
Standards	EN/IEC 60947-4-1 EN/IEC 60947-5-1 UL 60947-4-1 CSA C22.2 No 60947-4-1 JIS C8201-4-1 JIS C8201-5-1
Product Certifications	CB Scheme CCC cULus UKCA ATEX EU-RO-MR by DNV-GL EAC

Environment

IP degree of protection	IP2X front face with shrouds IEC 60529 IP2X front face with shrouds VDE 0106
Protective treatment	TH
Ambient air temperature for operation	-13...140 °F (-25...60 °C)
Ambient Air Temperature for Storage	-76...176 °F (-60...80 °C)
Permissible ambient air temperature around the device	-40...140 °F (-40...60 °C) at U _c
Adjustment of dial setting	-13...140 °F (-25...60 °C)
Mechanical robustness	Vibrations 5...300 Hz 6 gn contactor open Shocks 15 gn 11 ms contactor closed
Height	4.21 in (107 mm)
Width	4.13 in (105 mm)
Depth	4.96 in (126 mm)
Net Weight	1.98 lb(US) (0.9 kg)
Color	Dark grey

Ordering and shipping details

Category	22330-TESYS GIGA OVERLOAD RELAYS
Discount Schedule	I12
GTIN	3606481920270
Returnability	Yes

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.69 in (17.0 cm)
Package 1 Width	7.87 in (20.0 cm)
Package 1 Length	8.27 in (21.0 cm)

Package 1 Weight	3.12 lb(US) (1.416 kg)
Unit Type of Package 2	S03
Number of Units in Package 2	2
Package 2 Height	11.81 in (30.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	7.50 lb(US) (3.4 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

Recommended replacement(s)