

ECOR-1-BSC3/2X21 - Relay base

2907518

<https://www.phoenixcontact.com/us/products/2907518>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



ECOR-1... relay base, for miniature power relay or miniature switching relay with 1 or 2 changeover contacts, screw connection, plug-in option for input/interference suppression modules, for mounting on NS 35/7,5

Commercial data

Item number	2907518
Packing unit	1 pc
Minimum order quantity	10 pc
Sales key	C463
Product key	CK6312
GTIN	4055626214351
Weight per piece (including packing)	51.295 g
Weight per piece (excluding packing)	50.295 g
Customs tariff number	85366990
Country of origin	CN

ECOR-1-BSC3/2X21 - Relay base



2907518

<https://www.phoenixcontact.com/us/products/2907518>

Technical data

Product properties

Product type	Relay socket
Product family	ESSENTIAL edition

Electrical properties

Nominal voltage U_N	250 V AC/DC
Nominal current I_N	12 A

Connection data

Input side

Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section rigid	2x 0.2 mm ² ... 2.5 mm ² (without ferrule)
	2x 0.2 mm ² ... 1.5 mm ² (with ferrule)
Conductor cross section flexible	2x 0.2 mm ² ... 2.5 mm ² (without ferrule)
	2x 0.2 mm ² ... 1.5 mm ² (with ferrule)

Output side

Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section rigid	2x 0.2 mm ² ... 2.5 mm ² (without ferrule)
	2x 0.2 mm ² ... 1.5 mm ² (with ferrule)
Conductor cross section flexible	2x 0.2 mm ² ... 2.5 mm ² (without ferrule)
	2x 0.2 mm ² ... 1.5 mm ² (with ferrule)

Dimensions

Width	15.7 mm
Height	79.2 mm
Depth Retaining bracket	69 mm (ECOR-RH-1L)
	78 mm (ECOR-RH-1H)

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-25 °C ... 70 °C
Ambient temperature (storage/transport)	-25 °C ... 70 °C

Mounting

Mounting type	DIN rail mounting
Mounting position	any

ECOR-1-BSC3/2X21 - Relay base



2907518

<https://www.phoenixcontact.com/us/products/2907518>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2907518>



CSA

Approval ID: 255476



cUL Recognized

Approval ID: FILE E 113228



UL Recognized

Approval ID: FILE E 113228



EAC

Approval ID: RU C-DE.**08.B.01419

cULus Recognized

ECOR-1-BSC3/2X21 - Relay base



2907518

<https://www.phoenixcontact.com/us/products/2907518>

Classifications

ECLASS

ECLASS-11.0	27371603
ECLASS-12.0	27371603
ECLASS-13.0	27371603

ETIM

ETIM 8.0	EC001456
----------	----------

UNSPSC

UNSPSC 21.0	39122300
-------------	----------

ECOR-1-BSC3/2X21 - Relay base



2907518

<https://www.phoenixcontact.com/us/products/2907518>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

ECOR-1-BSC3/2X21 - Relay base

2907518


<https://www.phoenixcontact.com/us/products/2907518>

Mandatory accessories

REL-MR-BL- 12DC/21HC - Single relay

1109537

<https://www.phoenixcontact.com/us/products/1109537>




Pluggable miniature power relay in basic design, with power contact for high continuous currents, 1 changeover contact, input voltage 12 V DC

REL-MR-BL- 48DC/21HC - Single relay

1109538

<https://www.phoenixcontact.com/us/products/1109538>



Pluggable miniature power relay in basic design, with power contact for high continuous currents, 1 changeover contact, input voltage 48 V DC

ECOR-1-BSC3/2X21 - Relay base

2907518


<https://www.phoenixcontact.com/us/products/2907518>



REL-MR-BL-110DC/21HC - Single relay

1109539

<https://www.phoenixcontact.com/us/products/1109539>




Pluggable miniature power relay in basic design, with power contact for high continuous currents, 1 changeover contact, input voltage 110 V DC

REL-MR-BL- 24AC/21HC - Single relay

1109540

<https://www.phoenixcontact.com/us/products/1109540>



Pluggable miniature power relay in basic design, with power contact for high continuous currents, 1 changeover contact, input voltage 24 V AC

ECOR-1-BSC3/2X21 - Relay base

2907518


<https://www.phoenixcontact.com/us/products/2907518>



REL-MR-BL-115AC/21HC - Single relay

1109542

<https://www.phoenixcontact.com/us/products/1109542>




Pluggable miniature power relay in basic design, with power contact for high continuous currents, 1 changeover contact, input voltage 115 V AC

REL-MR-BL- 12DC/21-21 - Single relay

1109543

<https://www.phoenixcontact.com/us/products/1109543>



Pluggable miniature power relay in basic design, with power contact, 2 changeover contacts, input voltage 12 V DC

ECOR-1-BSC3/2X21 - Relay base

2907518


<https://www.phoenixcontact.com/us/products/2907518>



REL-MR-BL- 24DC/21-21 - Single relay

2906286

<https://www.phoenixcontact.com/us/products/2906286>



Plug-in miniature power relay in basic design, with power contact, 2 changeover contacts, input voltage 24 V DC

REL-MR-BL- 48DC/21-21 - Single relay

1109544

<https://www.phoenixcontact.com/us/products/1109544>



Pluggable miniature power relay in basic design, with power contact, 2 changeover contacts, input voltage 48 V DC

ECOR-1-BSC3/2X21 - Relay base

2907518


<https://www.phoenixcontact.com/us/products/2907518>



REL-MR-BL-110DC/21-21 - Single relay

1109545

<https://www.phoenixcontact.com/us/products/1109545>



Pluggable miniature power relay in basic design, with power contact, 2 changeover contacts, input voltage 110 V DC

REL-MR-BL- 24AC/21-21 - Single relay

1109546

<https://www.phoenixcontact.com/us/products/1109546>



Pluggable miniature power relay in basic design, with power contact, 2 changeover contacts, input voltage 24 V AC

ECOR-1-BSC3/2X21 - Relay base

2907518


<https://www.phoenixcontact.com/us/products/2907518>



REL-MR-BL-115AC/21-21 - Single relay

1109569

<https://www.phoenixcontact.com/us/products/1109569>




Plug-in miniature power relay in basic design, with power contact, 2 changeover contacts, input voltage 115 V AC

REL-MR-BL-230AC/21-21 - Single relay

2906287

<https://www.phoenixcontact.com/us/products/2906287>



Plug-in miniature power relay in basic design, with power contact, 2 changeover contacts, input voltage 230 V AC

ECOR-1-BSC3/2X21 - Relay base

2907518


<https://www.phoenixcontact.com/us/products/2907518>



REL-MR-BL- 24DC/21HC - Single relay

2906285

<https://www.phoenixcontact.com/us/products/2906285>




Plug-in miniature power relay in basic design, with power contact for high continuous currents, 1 changeover contact, input voltage 24 V DC

REL-MR-BL-230AC/21HC - Single relay

2906288

<https://www.phoenixcontact.com/us/products/2906288>



Plug-in miniature power relay in basic design, with power contact for high continuous currents, 1 changeover contact, input voltage 230 V AC

ECOR-1-BSC3/2X21 - Relay base

2907518

<https://www.phoenixcontact.com/us/products/2907518>



REL-MR-BL-24DC/21HC/MS - Single relay

2908180

<https://www.phoenixcontact.com/us/products/2908180>



Plug-in miniature relay, with power contact, 1 changeover contact, test button, mechanical switch position indicator, polarity: bipolar, input voltage: 24 V DC

REL-MR-BL-24DC/21-21/MS - Single relay

2908181

<https://www.phoenixcontact.com/us/products/2908181>



Plug-in miniature relay, with power contact, 2 changeover contacts, test button, mechanical switch position indicator, polarity: bipolar, input voltage: 24 V DC

Accessories

ECOR-1-BSC3/2X21 - Relay base

2907518

<https://www.phoenixcontact.com/us/products/2907518>



DB 50- 90 BU - Wire bridge

2821180

<https://www.phoenixcontact.com/us/products/2821180>

Flexible wire loop bridge, 50-pos., conductor cross-section: 0.5 mm², loop length: 90 mm, ferrule length: 8 mm, color: blue



DB 50- 90 BK - Wire bridge

2820916

<https://www.phoenixcontact.com/us/products/2820916>

Flexible wire loop bridge, 50-pos., conductor cross-section: 0.5 mm², loop length: 90 mm, ferrule length: 8 mm, color: black



ECOR-1-BSC3/2X21 - Relay base



2907518

<https://www.phoenixcontact.com/us/products/2907518>

DB 50- 90 GY - Wire bridge

2820929

<https://www.phoenixcontact.com/us/products/2820929>

Flexible wire loop bridge, 50-pos., conductor cross-section: 0.5 mm², loop length: 90 mm, ferrule length: 8 mm, color: gray



ECOR-RH-1L - Relay retaining bracket

2907524

<https://www.phoenixcontact.com/us/products/2907524>

Relay retaining bracket, with ejector function and integrated equipment marking area (7.5 x 15 mm), suitable for ECOR-1 relay base, for 16 mm tall miniature switching relays and solid-state relays



ECOR-1-BSC3/2X21 - Relay base

2907518

<https://www.phoenixcontact.com/us/products/2907518>



ECOR-RH-1H - Relay retaining bracket

2907523

<https://www.phoenixcontact.com/us/products/2907523>



Relay retaining bracket, with ejector function and integrated equipment marking area (7.5 x 15 mm), suitable for ECOR-1 relay base, for 25 mm tall miniature switching relays and solid-state relays

LDP- 12- 24DC - Plug-in module

2833657

<https://www.phoenixcontact.com/us/products/2833657>



Plug-in module, with freewheeling diode and yellow LED, polarity: **A1+**, **A2-**, input voltage: 12 ... 24 V DC $\pm 20\%$

ECOR-1-BSC3/2X21 - Relay base

2907518

<https://www.phoenixcontact.com/us/products/2907518>



DP-12-220 DC - Plug-in module

2907517

<https://www.phoenixcontact.com/us/products/2907517>



Plug-in module, with freewheeling diode, polarity: A1+, A2-, input voltage:
12 V DC ... 220 V DC $\pm 20\%$

LV-120-230AC/110DC - Plug-in module

2833738

<https://www.phoenixcontact.com/us/products/2833738>



Plug-in module, with varistor and yellow LED, input voltage: 120 ... 230 V AC /
110 V DC $\pm 20\%$

ECOR-1-BSC3/2X21 - Relay base

2907518

<https://www.phoenixcontact.com/us/products/2907518>



V-120-230UC - Plug-in module

2833880

<https://www.phoenixcontact.com/us/products/2833880>



Plug-in module, with varistor, input voltage: 120 ... 230 V AC/DC ± 20 %

RC-120-230UC - Plug-in module

2833767

<https://www.phoenixcontact.com/us/products/2833767>



Plug-in module, with RC element, input voltage: 120 ... 230 V AC/DC ± 20 %

ECOR-1-BSC3/2X21 - Relay base

2907518

<https://www.phoenixcontact.com/us/products/2907518>



MP 1 - Marker labels

2833631

<https://www.phoenixcontact.com/us/products/2833631>

Equipment marker, labeling surface 6 x 15 mm



Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA

586 Fulling Mill Road

Middletown, PA 17057, United States

(+717) 944-1300

info@phoenixcon.com