

# Product datasheet

Specifications



## Contactor, EasyPact TVS, 3P(3NO), AC-3, <=440V, 32A, 230V AC coil, 1NO auxiliary contact

LC1E3210P7

### Main

Range EasyPact

### Complementary

[I<sub>th</sub>] conventional free air thermal current 50 A (at 55 °C)

Tightening torque Control circuit: 1.2 N.m  
Power circuit: 2.1 N.m

### Environment

Permissible ambient air temperature around the device -20...70 °C at U<sub>c</sub>  
-60...80 °C storage  
-5...55 °C operation

### Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1 1

Package 1 Height 6.000 cm

Package 1 Width 8.700 cm

Package 1 Length 9.500 cm

Package 1 Weight 452.000 g

Unit Type of Package 2 S02

Number of Units in Package 2 24

Package 2 Height 15.000 cm

Package 2 Width 30.000 cm

Package 2 Length 40.000 cm

Package 2 Weight 11.380 kg

### Offer Sustainability

Sustainable offer status Green Premium product

REACH Regulation [REACH Declaration](#)

REACH free of SVHC Yes

EU RoHS Directive Compliant  
[EU RoHS Declaration](#)

<b>Toxic heavy metal free</b>	Yes
<b>Mercury free</b>	Yes
<b>China RoHS Regulation</b>	<a href="#">China RoHS declaration</a>
<b>RoHS exemption information</b>	Yes
<b>Environmental Disclosure</b>	<a href="#">Product Environmental Profile</a>
<b>WEEE</b>	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

**Recommended replacement(s)**