

# Product datasheet

Specifications



## Opale socket-outlet 3P with shutters 6 A white

X2106WH

### Main

Range of product	Opale
Product or component type	Socket-outlet
Device presentation	Mechanism with central plate
Outlet poles configuration	3P with shutters
Colour tint	White
Quantity per set	Set of 10

### Complementary

Number of power socket outlets	1
Device mounting	Flush
Number of modules	2 modules
Rated current	6 A 16 A
[Ue] rated operational voltage	250 V AC/DC
Connections - terminals	Shrouded terminals
Material	PC/ABS
Surface finish	Satin
Fixing mode	By captive screws

### Environment

Environmental characteristic	Flame retardant
Standards	IS 1293:1988
IP degree of protection	IP20

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.1 cm
Package 1 Width	4.2 cm
Package 1 Length	2.1 cm

Package 1 Weight	34 g
Unit Type of Package 2	BB1
Number of Units in Package 2	280
Package 2 Height	215 cm
Package 2 Width	340 cm
Package 2 Length	445 cm
Package 2 Weight	9525 g

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Under investigation
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Recommended replacement(s)