



cartridge M200 - 2 analog voltage outputs

TMCR2AQ2V

Main

Range of product	Easy Modicon M200
Product or component type	Analogue output cartridge
Product compatibility	Easy Modicon M200

Complementary	
Analogue output number	2
Analogue output type	Voltage: 010 V
Analogue output resolution	12 bits
LSB value	2.44 mV 010 V voltage
Load type	Resistive
Load impedance ohmic	>= 2 kOhm
Conversion time	20 ms
Stabilisation time	40 ms
Absolute accuracy error	+/- 1 % of full scale +/- 0.3 % of full scale at 25 °C
Temperature drift	+/- 0.02 %FS/°C
Repeat accuracy	+/- 0.4 %FS
Non-linearity	+/- 0.01 %FS
Cross talk	<= 1 LSB
Type of cable	Twisted shielded pairs cable
Electrical connection	3 x 1.5 mm² 2 screw terminal blocks with pitch 3.81 mm adjustment for outputs
Maximum cable distance between devices	Twisted shielded pairs cable: <30 m for output
Insulation	Non-insulated between analogue output and internal logic
Height	41 mm
Depth	15 mm
Width	35 mm
Net weight	0.012 kg

Environment

|--|

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.6 cm
Package 1 Width	7.0 cm
Package 1 Length	3.5 cm
Package 1 Weight	20.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	75
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	3.07 kg
Unit Type of Package 3	P06
Number of Units in Package 3	1200
Package 3 Height	75 cm
Package 3 Width	60 cm
Package 3 Length	80 cm
Package 3 Weight	106 kg

Offer Sustainability

REACh Regulation	REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
China RoHS Regulation	China RoHS declaration	
RoHS exemption information	Yes	

Recommended replacement(s)