

SACB-16X0,5/ 3X1,0-50,0 PUR - Master cable ring



1503373

<https://www.phoenixcontact.com/in/products/1503373>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Master cable for sensor/actuator boxes, with PE conductor, unshielded, material PUR/PP, 19-pos., 16 x 0.50 mm² and 3 x 1.00 mm², length: 50 m

Commercial Data

Item number	1503373
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	BF3
Product Key	BF3ZBX
Catalog Page	Page 305 (C-2-2019)
GTIN	4017918896973
Weight per Piece (including packing)	9,404 g
Weight per Piece (excluding packing)	9,404 g
Customs tariff number	85444290
Country of origin	DE

SACB-16X0,5/ 3X1,0-50,0 PUR - Master cable ring



1503373

<https://www.phoenixcontact.com/in/products/1503373>

Technical Data

Product properties

Product type	Cable by the meter
Number of positions	19
Application	Distributor boxes
LED	No

Electrical properties

Nominal voltage U_N	300 V AC
	300 V DC


Material specifications

Color	jet black
-------	-----------

Cable/line

Cable length	50 m
--------------	------

PUR/PVC black [PUR]

Dimensional drawing	
Cable weight	183.7 kg/km
UL AWM Style	20549 (80°C/300 V)
Number of positions	19
Shielded	no
Cable type	PUR/PVC black [PUR]
Conductor structure signal line	28x 0.15 mm
AWG signal line	20
Conductor cross section	16x 0.5 mm ² (Signal line)
	3x 1 mm ² (power line)
Wire diameter incl. insulation	1.5 mm ±0.1 mm (Signal line)
	2.1 mm ±0.1 mm (power line)
External cable diameter	10.5 mm ±0.2 mm
Outer sheath, material	PUR
External sheath, color	black RAL 9005
Conductor material	Bare Cu litz wires
Material wire insulation	PVC
Single wire, color	brown, blue, green/yellow, white, green, yellow, gray, pink, red,

SACB-16X0,5/ 3X1,0-50,0 PUR - Master cable ring



1503373

<https://www.phoenixcontact.com/in/products/1503373>

	black, violet, gray/pink, red/blue, white/green, brown/green, white/yellow, yellow/brown, white/gray, gray/brown
Inner sheath thickness	≥ 0.15 mm
Thickness, outer sheath	≥ 0.76 mm
Overall twist	Wires twisted in layers
Nominal voltage, cable	300 V
Test voltage	2000 V
Minimum bending radius, fixed installation	7.5 x D
Minimum bending radius, flexible installation	10 x D
Max. bending cycles	1500000
Flame resistance	according to DIN EN 50265
Resistance to oil	according to VDE 0472 Part 803
Other resistance	Highly resistant to acids, alkaline solutions and solvents
Special properties	Silicone-free
Ambient temperature (operation)	-40 °C ... 90 °C (cable, fixed installation) -5 °C ... 80 °C (Cable, flexible installation)

SACB-16X0,5/ 3X1,0-50,0 PUR - Master cable ring



1503373

<https://www.phoenixcontact.com/in/products/1503373>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/in/products/1503373>



EAC-RoHS

Approval ID: RU D-DE.HB35.B.00385

SACB-16X0,5/ 3X1,0-50,0 PUR - Master cable ring



1503373

<https://www.phoenixcontact.com/in/products/1503373>

Classifications

ECLASS

ECLASS-11.0	27060106
ECLASS-12.0	27060106
ECLASS-13.0	27060106

ETIM

ETIM 8.0	EC003250
----------	----------

UNSPSC

UNSPSC 21.0	26121600
-------------	----------

SACB-16X0,5/ 3X1,0-50,0 PUR - Master cable ring



1503373

<https://www.phoenixcontact.com/in/products/1503373>

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

SACB-16X0,5/ 3X1,0-50,0 PUR - Master cable ring

1503373

<https://www.phoenixcontact.com/in/products/1503373>

Accessories

WIREFOX-D 13 - Stripping tool

1212162

<https://www.phoenixcontact.com/in/products/1212162>



Stripping tool, for stripping installation lines of \varnothing 8 - 13 mm , e.g. NYM 3 x 1.5 mm² to 5 x 2.5 mm², single line stripping 0.2 mm² - 4 mm² , with longitudinal cut blade and sliding knife

WIREFOX-D 40 - Stripping tool

1212161

<https://www.phoenixcontact.com/in/products/1212161>



Stripping tool, for stripping cables of 4.5 mm - 40 mm- \varnothing , insulation thickness of up to 4.5 mm, pivoting blade for round, lengthwise, and spiral cuts

SACB-16X0,5/ 3X1,0-50,0 PUR - Master cable ring



1503373

<https://www.phoenixcontact.com/in/products/1503373>

WIREFOX 4 - Stripping tool

1212156

<https://www.phoenixcontact.com/in/products/1212156>



Stripping tool, for cables and conductors (especially for rubber and silicone insulations) from 0.1 - 4 mm², self-adjusting, stripping length of up to 18 mm, cutting capacity of up to 10 mm² stranded/1.5 mm² solid, replaceable stripping blade

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.

A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420

info@phoenixcontact.co.in