

WP-G HF IP66 M20 BK - Screw connection



3240898

<https://www.phoenixcontact.com/in/products/3240898>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

Cable gland, metric thread, IP66 protection, straight



Commercial Data

Item number	3240898
Packing unit	50 pc
Minimum order quantity	50 pc
Sales Key	BF7
Product Key	BF7DSA
Catalog Page	Page 587 (C-3-2019)
GTIN	4046356710053
Weight per Piece (including packing)	11.456 g
Weight per Piece (excluding packing)	11.468 g
Customs tariff number	39174000
Country of origin	DE

3240898

<https://www.phoenixcontact.com/in/products/3240898>

Technical Data

Product properties

Product type	Corrugated pipe screw connection
Application	Cable gland
Type of the screw connection	Conduit adapter
Type	Outer thread
Cable outlet	straight
Thread type	metric

Dimensions

Width	29.5 mm
Height	44.5 mm

External dimensions

Outside diameter	16.5 mm
------------------	---------

Material specifications

Color	black
Material	PA 6
Flammability rating according to UL 94	V0
Material for screw connection	PA
Components	free from silicone, halogen, and cadmium

Cable/line

Halogen-free	yes
--------------	-----

Mechanical properties

Mechanical data

Type of the screw connection	Conduit adapter
------------------------------	-----------------

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP66
Ambient temperature (operation)	-40 °C ... 120 °C

Mounting

Wrench size	27 mm
-------------	-------

WP-G HF IP66 M20 BK - Screw connection



3240898

<https://www.phoenixcontact.com/in/products/3240898>

Approvals



UL Recognized



LR



VDE Zeichengenehmigung

WP-G HF IP66 M20 BK - Screw connection



3240898

<https://www.phoenixcontact.com/in/products/3240898>

Classifications

ECLASS

ECLASS-11.0	27430311
ECLASS-12.0	27430311
ECLASS-12.0	27430311

ETIM

ETIM 8.0	EC001469
----------	----------

UNSPSC

UNSPSC 21.0	39121300
-------------	----------

WP-G HF IP66 M20 BK - Screw connection



3240898

<https://www.phoenixcontact.com/in/products/3240898>

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

WP-G HF IP66 M20 BK - Screw connection



3240898

<https://www.phoenixcontact.com/in/products/3240898>

Accessories

WP-PA HF 21,2 BK - Protective hose

3240683

<https://www.phoenixcontact.com/in/products/3240683>



Protective hose, material: PA 6, UV-resistant: yes, flexible, degree of protection: IP68, color: black, flammability rating in acc. with UL 94: V0, inner diameter: 17 mm, Total length: 50 m

WP-PA HF-HB 21,2 BK - Protective hose

3240841

<https://www.phoenixcontact.com/in/products/3240841>



Protective hose, material: PA 6, UV-resistant: yes, flexible, degree of protection: IP68, color: black, flammability rating in acc. with UL 94: HB, inner diameter: 17 mm, Total length: 50 m

WP-G HF IP66 M20 BK - Screw connection

3240898

<https://www.phoenixcontact.com/in/products/3240898>



WP-BASE A M20 - Protective hose fixing bracket

3241084

<https://www.phoenixcontact.com/in/products/3241084>



Fixing bracket for protective sleeves, fixed with two screws

WP-OR M20 - Sealing ring

3241190

<https://www.phoenixcontact.com/in/products/3241190>



Sealing ring, for threads M20, color: black

WP-G HF IP66 M20 BK - Screw connection



3240898

<https://www.phoenixcontact.com/in/products/3240898>

A-INL-M20-P-BK - Counter nut

1411215

<https://www.phoenixcontact.com/in/products/1411215>

Counter nut, for threads M20 x 1.5, color: jet black



Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.

A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420

info@phoenixcontact.co.in