

SAC-5P-100,0-PUR/0,34 - Cable reel



1501676

<https://www.phoenixcontact.com/in/products/1501676>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

By the meter, Cable reel, PUR halogen-free, black-gray RAL 7021, 5-wire, color single wire: brown, white, blue, black, green-yellow, cable length: 100 m



Commercial Data

Item number	1501676
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	BF1
Product Key	BF1LBA
Catalog Page	Page 302 (C-2-2019)
GTIN	4017918813369
Weight per Piece (including packing)	3,201 g
Weight per Piece (excluding packing)	3,036 g
Customs tariff number	85444995
Country of origin	DE

SAC-5P-100,0-PUR/0,34 - Cable reel



1501676

<https://www.phoenixcontact.com/in/products/1501676>

Technical Data

Product properties

Product type	Cable by the meter
Number of positions	5
Application	Connector
Shielded	no

Cable/line

Cable length	100 m
--------------	-------

PUR halogen-free black [PUR]

Cable weight	33 kg/km
UL AWM Style	20549
Number of positions	5
Shielded	no
Cable type	PUR halogen-free black [PUR]
Conductor structure signal line	42x 0.10 mm
AWG signal line	22
Conductor cross section	5x 0.34 mm ² (Signal line)
Wire diameter incl. insulation	1.27 mm 0.05 mm (Signal line)
External cable diameter	4.55 mm ±0.15 mm
Outer sheath, material	PUR
External sheath, color	black-gray RAL 7021
Conductor material	Bare Cu litz wires
Material wire insulation	PP
Single wire, color	brown, white, blue, black, green-yellow
Thickness, insulation	approx. 0.5 mm
Max. conductor resistance	max. 58 Ω/km (at 20 °C)
Insulation resistance	≥ 16 GΩ*km (at 20 °C)
Nominal voltage, cable	300 V
Test voltage	3000 V
Smallest bending radius, fixed installation	23 mm
Smallest bending radius, movable installation	46 mm
Max. bending cycles	4000000
Halogen-free	in accordance with DIN VDE 0472 part 815
Flame resistance	in accordance with UL 758/1581 FT2 DIN EN 60332-2-2 (20 s)
Resistance to oil	in accordance with DIN EN 60811-2-1
Other resistance	Highly resistant to acids, alkaline solutions and solvents hydrolysis and microbe resistant Resistant to salt water partly UV-resistant in accordance with DIN EN ISO 4892-2-A

Flexible cable conduit capable

SAC-5P-100,0-PUR/0,34 - Cable reel



1501676

<https://www.phoenixcontact.com/in/products/1501676>

Special properties	Silicone-free
	Free of substances which would hinder coating with paint or varnish
	flexible
Ambient temperature (operation)	-40 °C ... 80 °C (cable, fixed installation)
	-25 °C ... 80 °C (Cable, flexible installation)

SAC-5P-100,0-PUR/0,34 - Cable reel



1501676

<https://www.phoenixcontact.com/in/products/1501676>

Approvals



EAC

Approval ID: RU D-DE.HB35.B.00371

SAC-5P-100,0-PUR/0,34 - Cable reel



1501676

<https://www.phoenixcontact.com/in/products/1501676>

Classifications

ECLASS

ECLASS-11.0	27061801
ECLASS-12.0	27061801
ECLASS-13.0	27061801

ETIM

ETIM 8.0	EC003249
----------	----------

UNSPSC

UNSPSC 21.0	26121600
-------------	----------

SAC-5P-100,0-PUR/0,34 - Cable reel



1501676

<https://www.phoenixcontact.com/in/products/1501676>

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

SAC-5P-100,0-PUR/0,34 - Cable reel



1501676

<https://www.phoenixcontact.com/in/products/1501676>

Accessories

WIREFOX SAC - Stripping tool

1212623

<https://www.phoenixcontact.com/in/products/1212623>



Stripping pliers, for halogen-free sensor/actuator cables (SAC cables), with PUR and PVC insulation, from Ø of 4.4 to 7 mm, any stripping length

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.
A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420
info@phoenixcontact.co.in