

Product datasheet

Specifications



Isoblock interlocked socket - 63 A - 3P + N + E - 380...415 V AC - IP65 - wall

82783

Main

| | |
|---------------------------|--------------------|
| Range | PratiKa |
| Product or component type | Interlocked socket |
| Device short name | Isoblock socket |
| Plug, socket category | Low voltage |
| Industrial socket type | B32/63 |
| Poles description | 3P + N + E |
| Network type | AC |
| Outlet standard | Industrial |

Complementary

| | |
|--------------------------------|---|
| Mounting mode | Wall-mounted |
| [In] rated current | 63 A |
| [Ue] rated operational voltage | 380...415 V |
| Network frequency | 50/60 Hz |
| Ground lug clockwise position | 6 h |
| Protection type | Without protection |
| Product compatibility | Modular device |
| Total number of 18 mm modules | 6 |
| Plug, socket material | Housing: self-extinguishing engineering polymer |
| Contacts material | Sleeves: nickel plated brass |
| Connections - terminals | Captive screws |
| Maximum cable cross section | 35 mm ² |
| Maximum cable outer diameter | 25 mm |
| Cable entry | Cable gland |
| Thread type | Pg 29 |
| Net weight | 2.426 kg |
| Base dimension | 144 x 389 mm |
| Height | 389 mm |
| Width | 144 mm |

| | |
|----------------|-----------------|
| Depth | 147 mm |
| Colour | Grey (RAL 7035) |
| Voltage colour | Red |

Environment

| | |
|---------------------------------------|---|
| Standards | IEC 60309-1 IEC 60309-2 |
| IP degree of protection | IP65 conforming to IEC 60529 |
| IK degree of protection | IK10 conforming to EN 62262 |
| Fire resistance | 850 °C conforming to IEC 60695-2-11 |
| Relative humidity | 50 % at 40 °C 70 % at 30 °C 90 % at 20 °C |
| Ambient air temperature for operation | 35 °C (86400 s) -25...40 °C |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 15.4 cm |
| Package 1 Width | 15.4 cm |
| Package 1 Length | 41.5 cm |
| Package 1 Weight | 2.422 kg |
| Unit Type of Package 2 | P12 |
| Number of Units in Package 2 | 12 |
| Package 2 Height | 27.5 cm |
| Package 2 Width | 80.0 cm |
| Package 2 Length | 120.0 cm |
| Package 2 Weight | 41.064 kg |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Recommended replacement(s)