

1619629

https://www.phoenixcontact.com/in/products/1619629

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



M23, Cable connector, CA, straight, shielded: yes, Screw locking, No. of pos.: 17, Direction of rotation: Standard, type of contact: Socket, Crimp connection, cable diameter range: 3 mm ... 14. 5 mm, coding:N, Alternative product in accordance with RoHS II without Exemption 6c (Pb <0. 1%) item no.: 1243718

Commercial Data

Item number	1619629
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	ABR
Product Key	ABRBFA
Catalog Page	Page 110 (C-2-2019)
GTIN	4046356822497
Weight per Piece (including packing)	94.5 g
Weight per Piece (excluding packing)	91.2 g
Customs tariff number	85366990
Country of origin	DE



1619629

https://www.phoenixcontact.com/in/products/1619629

Technical Data

	Order information:	Order 17 x 1 mm crimp contacts separately
Pr	oduct properties	
	Product type	Circular connector (cable-side)

Connector

Connection 1

Head design	Socket
Insulating body	
Note	Order information: Order crimp contacts Ø 1 mm separately
Coding	N
Insulation body material	PA 6.6
Connection method	Crimp connection
Contact type	Socket
Application	Feedback, signal
	Signal
Number of positions	17
Direction of rotation	Standard
Connection profile	17
Contact diameter Signal contacts	1 mm
Litz wire cross-section Signal contacts min.	0.06 mm²
Litz wire cross-section Signal contacts max.	1 mm²
Nominal current per signal contact	8 A
Rated voltage Signal contact	48 V AC
Rated surge voltage	1.5 kV
Overvoltage category	III
Degree of pollution	3

Housing

Housing material	Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)
Type of locking	Screw locking
Pg screw connection	none
Degree of protection (plugged in)	IP67
Thread type	M23

Seal

	
External cable diameter	3 mm 14.5 mm
Seal material	FPM



1619629

https://www.phoenixcontact.com/in/products/1619629

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation) -40 °C ... 125 °C


1619629

https://www.phoenixcontact.com/in/products/1619629




Drawings

Schematic diagram



Contact chamber numbering (view of plug-in side), standard socket

Dimensional drawing





1619629

https://www.phoenixcontact.com/in/products/1619629

Approvals

. 71 2	cUL Recognized Approval ID: E335019-2	20141210			
		Nominal Voltage U_N	Nominal Current I _N	Cross Section AWG	Cross Section mm ²
		48 V	5 A	- 18	-

UL Recognized Approval ID: E335019-20141210					
		Nominal Voltage U_N	Nominal Current I _N	Cross Section AWG	Cross Section mm ²
		48 V	8 A	- 18	-



1619629

https://www.phoenixcontact.com/in/products/1619629

Classifications

UNSPSC 21.0

ECLASS

	ECLASS-11.0	27440102
	ECLASS-12.0	27440116
	ECLASS-13.0	27440116
ETI	М	
	ETIM 8.0	EC002635
UN	SPSC	

39121400



1619629

https://www.phoenixcontact.com/in/products/1619629

Environmental Product Compliance

REACh SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"



1619629

https://www.phoenixcontact.com/in/products/1619629

Accessories

SF-6CS2000 - Crimp contact

1605562

https://www.phoenixcontact.com/in/products/1605562



Crimp contact, Socket, turned, Single contact, contact diameter: 1 mm, crimp range: $0.06~\text{mm}^2$... $0.25~\text{mm}^2$, Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1241922

SF-10KS004 - Crimp contact

1607356

https://www.phoenixcontact.com/in/products/1607356



Crimp contact, Socket, turned, Single contact, contact diameter: 1 mm, crimp range: $0.14~\text{mm}^2$... $0.5~\text{mm}^2$, Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1241922



1619629

https://www.phoenixcontact.com/in/products/1619629

SF-6AS2000 - Crimp contact

1605557

https://www.phoenixcontact.com/in/products/1605557



Crimp contact, Socket, turned, Single contact, contact diameter: 1 mm, crimp range: $0.25~\text{mm}^2$... 1 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1241922

RC-Z2058 - Protective cap

1604223

https://www.phoenixcontact.com/in/products/1604223



Plastic protection cap for connectors with M23 knurled nut



1619629

https://www.phoenixcontact.com/in/products/1619629

RC-Z2468 - Protective cap

1611796

https://www.phoenixcontact.com/in/products/1611796



Plastic protection cap, antistatic, for connectors with M23 knurled nut

CA-Z0077 - Metal protective cap

1627224

https://www.phoenixcontact.com/in/products/1627224



Metal protective cap, degree of protection: IP67, Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1245447



1619629

https://www.phoenixcontact.com/in/products/1619629

RF-Z0014 - Color-coding

1620588

https://www.phoenixcontact.com/in/products/1620588

Color-coding, color: green



RF-Z0015 - Color-coding

1620592

https://www.phoenixcontact.com/in/products/1620592

Color-coding, color: orange





1619629

https://www.phoenixcontact.com/in/products/1619629

RF-Z0016 - Color-coding

1620593

https://www.phoenixcontact.com/in/products/1620593

Color-coding, color: black



SF-Z0028 - Torque screwdriver

1607456

https://www.phoenixcontact.com/in/products/1607456



Torque screwdriver, series: RC



1619629

https://www.phoenixcontact.com/in/products/1619629

SF-Z0027 - Hook wrench

1607455

https://www.phoenixcontact.com/in/products/1607455



Hook wrench, series: RC

RF-Z0003 - Square mounting flange

1607905

https://www.phoenixcontact.com/in/products/1607905



Square mounting flange, Axial seal, 4xM3, flange dimensions: 35 mm x 35 mm, series: RF, Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1242369

Phoenix Contact 2023 @ - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT (I) Pvt. Ltd. A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420 info@phoenixcontact.co.in