

# Product datasheet

Specifications



## EasyPact TVS contactor 3P(3 NO) - AC-3 - <= 440 V 6A - 220 V AC coil

LC1E0610M7

### Main

|                                |   |
|--------------------------------|---|
| Range                          | EasyPact  |
| Product or component type      | Contactor   |
| Device short name              | LC1E  |
| Contactor application          | Motor control<br>Resistive load   |
| Utilisation category           | AC-3<br>AC-1  |
| Poles description              | 3P  |
| [Ue] rated operational voltage | Power circuit: <= 690 V AC 50/60 Hz   |
| [Ie] rated operational current | 6 A (at <55 °C) at <= 440 V AC AC-3 for power circuit<br>20 A (at <55 °C) at <= 440 V AC AC-1 for power circuit |
| [Uc] control circuit voltage   | 220 V AC 50/60 Hz   |

### Complementary

|  |  |
|--|--|
| Motor power kW   | 1.1 kW at 220...230 V AC 50/60 Hz<br>2.2 kW at 380...400 V<br>2.2 kW at 415 V<br>2.2 kW at 440 V<br>3 kW at 500 V<br>3 kW at 660...690 V             |
| Pole contact composition                                 | 3 NO   |
| [I <sub>th</sub> ] conventional free air thermal current | 16 A (at 60 °C) for power circuit  |
| I <sub>rms</sub> rated making capacity                   | 60 A at 440 V AC for power circuit conforming to IEC 60947-4-1   |
| Rated breaking capacity                                  | 48 A at 440 V for power circuit conforming to IEC 60947  |
| [I <sub>cw</sub> ] rated short-time withstand current    | 80 A 40 °C - 10 s for power circuit<br>45 A 40 °C - 60 s for power circuit<br>20 A 40 °C - 600 s for power circuit                                   |
| Associated fuse rating                                   | 10 A gG at <= 690 V coordination type 1 for control circuit conforming to IEC 60947-5-1<br>12 A gG at <= 690 V coordination type 1 for power circuit |
| Average impedance  | 2.5 mOhm - I <sub>th</sub> 20 A 50 Hz for power circuit  |
| Power dissipation per pole                               | 0.09 W AC-3<br>1 W AC-1  |
| [Ui] rated insulation voltage                            | 690 V conforming to IEC 60947-4-1  |
| Overtoltage category                                     | III  |
| Pollution degree   | 3  |

|   |  |
|---|--|
| <b>[Uimp] rated impulse withstand voltage</b> | 6 kV coil not connected to the power circuit conforming to IEC 60947   |
| <b>Mechanical durability</b>                  | 10000000 cycles  |
| <b>Electrical durability</b>                  | 1400000 cycles AC-3<br>150000 cycles AC-1  |
| <b>Control circuit type</b>                   | AC at 50/60 Hz   |
| <b>Control circuit voltage limits</b>         | 0.85...1.1 U <sub>c</sub> (55 °C):operational 50/60 Hz<br>0.3...0.6 U <sub>c</sub> (55 °C):drop-out 50/60 Hz   |
| <b>Inrush power in VA</b>                     | 95 VA 50 Hz cos phi 0.75 (at 20 °C)<br>95 VA 60 Hz cos phi 0.75 (at 20 °C)   |
| <b>Hold-in power consumption in VA</b>        | 8.3 VA 50 Hz cos phi 0.3 (at 20 °C)<br>8.5 VA 60 Hz cos phi 0.3 (at 20 °C)   |
| <b>Heat dissipation</b>                       | 2...3 W for control circuit  |
| <b>Operating time</b>                         | 12...22 ms on closing<br>4...19 ms on opening  |
| <b>Maximum operating rate</b>                 | 1800 cyc/h 60 °C   |
| <b>Connections - terminals</b>                | Power circuit: screw clamp terminals 1 1...4 mm <sup>2</sup> - cable stiffness: flexible with cable end<br>Power circuit: screw clamp terminals 2 1...2.5 mm <sup>2</sup> - cable stiffness: flexible with cable end<br>Power circuit: screw clamp terminals 1 1...4 mm <sup>2</sup> - cable stiffness: solid without cable end<br>Power circuit: screw clamp terminals 2 1...4 mm <sup>2</sup> - cable stiffness: solid without cable end<br>Control circuit: screw clamp terminals 1 1...4 mm <sup>2</sup> - cable stiffness: flexible without cable end<br>Control circuit: screw clamp terminals 2 1...4 mm <sup>2</sup> - cable stiffness: flexible without cable end<br>Control circuit: screw clamp terminals 1 1...4 mm <sup>2</sup> - cable stiffness: flexible with cable end<br>Control circuit: screw clamp terminals 2 1...2.5 mm <sup>2</sup> - cable stiffness: flexible with cable end<br>Control circuit: screw clamp terminals 1 1...4 mm <sup>2</sup> - cable stiffness: solid without cable end<br>Control circuit: screw clamp terminals 2 1...4 mm <sup>2</sup> - cable stiffness: solid without cable end |
| <b>Tightening torque</b>                      | Power circuit: 1.2 N.m<br>Control circuit: 1.2 N.m   |
| <b>Auxiliary contact composition</b>          | 1 NO   |
| <b>Minimum switching voltage</b>              | 17 V for control circuit   |
| <b>Minimum switching current</b>              | 5 mA for control circuit   |
| <b>Insulation resistance</b>                  | > 10 MOhm for control circuit  |
| <b>Non-overlap time</b>                       | 1.5 ms on energisation guaranteed between NC and NO contact<br>1.5 ms on de-energisation guaranteed between NC and NO contact  |
| <b>Mounting support</b>                       | Plate<br>DIN rail  |

## Environment

|  |   |
|--|---|
| <b>Standards</b>   | IEC 60947-5-1<br>IEC 60947-1<br>IEC 60947-4-1   |
| <b>Product certifications</b>                                | CE<br>EAC   |
| <b>IP degree of protection</b>                               | IP2X conforming to IEC 60529  |
| <b>Protective treatment</b>                                  | TH (pollution degree 3) conforming to IEC 60068-2-30  |
| <b>Permissible ambient air temperature around the device</b> | -20...70 °C at U <sub>c</sub><br>-60...80 °C storage<br>-5...55 °C operation  |
| <b>Operating altitude</b>                                    | 3000 m without derating   |
| <b>Fire resistance</b>                                       | 850 °C conforming to IEC 60695-2-1  |
| <b>Mechanical robustness</b>                                 | Vibrations contactor open (1.5 Gn, 5...300 Hz)<br>Vibrations contactor closed (3 Gn, 5...300 Hz)<br>Shocks contactor open (7 Gn for 11 ms)<br>Shocks contactor closed (10 Gn for 11 ms) |
| <b>Height</b>  | 74 mm   |
| <b>Width</b>   | 45 mm   |
| <b>Depth</b>   | 80 mm   |

|            |        |
|------------|--------|
| Net weight | 0.3 kg |
|------------|--------|

## Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 8.5 cm    |
| Package 1 Width              | 5 cm      |
| Package 1 Length             | 7.5 cm    |
| Package 1 Weight             | 349 g     |
| Unit Type of Package 2       | S02       |
| Number of Units in Package 2 | 36        |
| Package 2 Height             | 15 cm     |
| Package 2 Width              | 30 cm     |
| Package 2 Length             | 40 cm     |
| Package 2 Weight             | 13.033 kg |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| REACH free of SVHC         | Yes   |
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a>  |
| Toxic heavy metal free     | Yes   |
| Mercury free               | Yes   |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a>  |
| RoHS exemption information | <a href="#">Yes</a>   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

## Recommended replacement(s)