

ECOR-3-BSC1-RT/3X21 - Relay base



2907522

<https://www.phoenixcontact.com/in/products/2907522>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



ECOR-3 relay base, for octal relays with three changeover contacts, bolt connection, for mounting on NS 35/7,5

Commercial Data

Item number	2907522
Packing unit	10 pc
Minimum order quantity	10 pc
Sales Key	CK6
Product Key	CK6314
GTIN	4055626214399
Weight per Piece (including packing)	60.27 g
Weight per Piece (excluding packing)	60.27 g
Customs tariff number	85366990
Country of origin	CN

Technical Data

Product properties

Product family	ESSENTIAL edition
----------------	-------------------

Electrical properties

Nominal voltage U_N	250 V AC/DC
Nominal current I_N	10 A

Connection data

Input side

Connection method	Bolt connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section rigid	2x 0.2 mm ² ... 2.5 mm ² (without ferrule)
	2x 0.2 mm ² ... 1.5 mm ² (with ferrule)
Conductor cross section flexible	2x 0.2 mm ² ... 2.5 mm ² (without ferrule)
	2x 0.2 mm ² ... 1.5 mm ² (with ferrule)

Output side

Connection method	Bolt connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section rigid	2x 0.2 mm ² ... 2.5 mm ² (without ferrule)
	2x 0.2 mm ² ... 1.5 mm ² (with ferrule)
Conductor cross section flexible	2x 0.2 mm ² ... 2.5 mm ² (without ferrule)
	2x 0.2 mm ² ... 1.5 mm ² (with ferrule)

Dimensions

Width	42.3 mm
Height	54.7 mm
Depth Retaining bracket	91 mm (EL3-M52)

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-25 °C ... 55 °C
Ambient temperature (storage/transport)	-25 °C ... 55 °C

Mounting

Mounting type	DIN rail mounting
Mounting position	any

ECOR-3-BSC1-RT/3X21 - Relay base



2907522

<https://www.phoenixcontact.com/in/products/2907522>

Approvals



CSA

Approval ID: 255476



cUL Recognized

Approval ID: FILE E 113228



UL Recognized

Approval ID: FILE E 113228



EAC

Approval ID: RU C-DE.**08.B.01419

ECOR-3-BSC1-RT/3X21 - Relay base



2907522

<https://www.phoenixcontact.com/in/products/2907522>

Classifications

ECLASS

ECLASS-11.0	27371603
ECLASS-12.0	27371603
ECLASS-13.0	27371603

ETIM

ETIM 8.0	EC001456
----------	----------

UNSPSC

UNSPSC 21.0	39122300
-------------	----------

ECOR-3-BSC1-RT/3X21 - Relay base



2907522

<https://www.phoenixcontact.com/in/products/2907522>

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

ECOR-3-BSC1-RT/3X21 - Relay base

2907522

<https://www.phoenixcontact.com/in/products/2907522>

Accessories

EL3-M52 - Relay retaining bracket

2833628

<https://www.phoenixcontact.com/in/products/2833628>



Relay retaining bracket, wiring to suit relay base RIF-3 and PR3, for 52 mm high octal relay

DB 50- 90 BU - Wire bridge

2821180

<https://www.phoenixcontact.com/in/products/2821180>

Flexible wire loop bridge, 50-pos., conductor cross-section: 0.5 mm², loop length: 90 mm, ferrule length: 8 mm, color: blue



ECOR-3-BSC1-RT/3X21 - Relay base



2907522

<https://www.phoenixcontact.com/in/products/2907522>

DB 50- 90 BK - Wire bridge

2820916

<https://www.phoenixcontact.com/in/products/2820916>

Flexible wire loop bridge, 50-pos., conductor cross-section: 0.5 mm², loop length: 90 mm, ferrule length: 8 mm, color: black



DB 50- 90 GY - Wire bridge

2820929

<https://www.phoenixcontact.com/in/products/2820929>

Flexible wire loop bridge, 50-pos., conductor cross-section: 0.5 mm², loop length: 90 mm, ferrule length: 8 mm, color: gray



ECOR-3-BSC1-RT/3X21 - Relay base

2907522

<https://www.phoenixcontact.com/in/products/2907522>

REL-OR-BL/L- 12DC/3X21 - Single relay

1109565

<https://www.phoenixcontact.com/in/products/1109565>



Plug-in octal relay in basic design with power contacts, 3 changeover contacts, test button, status LED, mechanical switch position indicator, polarity A1+, A2-, input voltage: 12 V DC

REL-OR-BL- 24DC/3X21 - Single relay

1032532

<https://www.phoenixcontact.com/in/products/1032532>



Plug-in octal relays in basic design with power contacts, 3 changeover contacts, test button, mechanical switch position indicator, polarity: A1+, A2-, input voltage: 24 V DC

ECOR-3-BSC1-RT/3X21 - Relay base

2907522

<https://www.phoenixcontact.com/in/products/2907522>

REL-OR-BL/L-125DC/3X21 - Single relay

1109566

<https://www.phoenixcontact.com/in/products/1109566>



Plug-in octal relay in basic design with power contacts, 3 changeover contacts, test button, status LED, mechanical switch position indicator, polarity A1+, A2-, input voltage: 125 V DC

REL-OR-BL/L- 24AC/3X21 - Single relay

1109567

<https://www.phoenixcontact.com/in/products/1109567>



Plug-in octal relay in basic design with power contacts, 3 changeover contacts, test button, status LED, mechanical switch position indicator, input voltage: 24 V AC

ECOR-3-BSC1-RT/3X21 - Relay base



2907522

<https://www.phoenixcontact.com/in/products/2907522>

REL-OR-BL/L-115AC/3X21 - Single relay

1109568

<https://www.phoenixcontact.com/in/products/1109568>



Plug-in octal relay in basic design with power contacts, 3 changeover contacts, test button, status LED, mechanical switch position indicator, input voltage: 115 V AC

REL-OR-BL-230AC/3X21 - Single relay

1032537

<https://www.phoenixcontact.com/in/products/1032537>



Plug-in octal relays in basic design with power contacts, 3 changeover contacts, test button, mechanical switch position indicator, input voltage: 230 V AC

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.
A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420
info@phoenixcontact.co.in