

Product: GDM 2011 J black ☑




DIN Valve Connector, Form A, Field Attachable, 2+Ground, PG 11, Black Housing, without circuitry, UL, 250 V


Product Description


GDM - 175301-803 (DIN 43650), Form A, Female, 18mm, Black housing, 2+Ground (Protective Earth). screw contacts, without circuitry, 250 V AC/DC, 16A, cable gland PG11 thread, UL


Technical Drawing














Technical Specifications

Technical Data

Product Family:	Valve Connectors			
Product Sub Family:	GDM Legacy			
Brand:	Hirschmann			
Connector Type:	Field Attachable			
Type of Contact / Gender:	Female			
Connector Design:	Angled			
Number of Pins:	2+PE (PE across cable outlet)			
Coding:	A			
Shielding:	Unshielded			
Attachment Type:	Central Screw			
Rated Voltage:	250 V			
Rated Impulse Voltage:	4.0 kV			
Rated Current*:	16 A			
Contact Resistance:	≤ 10 mOhm			
Insulation Resistance:	> 10^9 Ohm			
Mating Cycles:	≤ 50			
Cable Gland:	PG11			
Conductor Cross Section:	0.25 - 1.5 mm ²			
Suitable Cables:	itable Cables: Ø 6 - 9 mm			

Ambient Temperature (Operation)*:	-40 °C - +125 °C
Protection Degree / IP Rating**:	IP65
Design Standard:	DIN EN 175301-803-A, ISO 4400
Pollution Degree:	3 acc. to DIN EN 60664-1 (VDE 0110-1)
Clearance / Creepage Distance:	DIN EN 60664-1 (2008/01); VDE 0110-1
Overvoltage Category:	III acc. to DIN EN 60664-1 (VDE 0110-1)

Materials

Contact Base Material:	CuZn			
Contact Plating:	Cu/Sn			
Contact Bearer Color:	Brown			
Flammability Class (Contact Bearer):	UL 94 V-0			
Housing Color:	Black			
Flammability Class (Housing):	IL 94 HB			
Cable Gland Material:	PA GF			
Cable Gland Gasket:	NBR			
Cable Gland Color:	Black			
Attachment Material:	Steel, Philips combi slot			
Gasket Material:	Sold separately			

Additional Technical Data

Fastening Torque (Contact Screw):	(40-50) Ncm for conductor size 0.25 - 1.5 mm²; (30-40) Ncm for conductor size 0.34 mm²; (25-30) Ncm for conductor size 0.25 mm²
Fastening Torque (Cable Gland):	(250-375) Ncm
Fastening Torque (Attachment):	(50-60) Ncm

Approvals

UL-File:	E95522
VDE:	Yes
SEV:	Yes

Safety & Environmental Compliance

|--|

Notes

Note Derating:	Notice derating
Protection Degree / IP Rating Note:	** only if mounted and locked in combination with Hirschmann / Lumberg Automation connector.

Variants

	Item #	Item Description	Central Screw	Gasket	Packaging	Replaced By
	932106100	GDM 2011 J black	1- SteelScrew, Combi Head	0 - Sold Seperately	F - Collect packaging 200 pieces, assembled	ID: 934888123 Name: GDM21AN-A0U-10F

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.