Product datasheet

Specifications



alarm switch AL, EasyPact EZC 100, EasyPact CVS 100BS, 1 common point changeover contact

EZAUX01

VI	а	ı	r	1

Range of product	EZC100
Range	EasyPact
Device short name	AL
Product or component type	Switch
Device application	Alarm
Range compatibility	EasyPact (EZC) circuit breaker
Signal contacts composition	1 NO/NC

Complementary

Auxiliary contacts type	Standard
[Ith] conventional free air thermal current	5 A
[le] rated operational current	AC-12: 3 A at 250 V AC 50/60 Hz AC-12: 5 A at 125 V AC 50/60 Hz AC-12: 5 A at 24 V AC 50/60 Hz AC-12: 5 A at 48 V AC 50/60 Hz AC-15: 2 A at 250 V AC 50/60 Hz AC-15: 3 A at 125 V AC 50/60 Hz AC-15: 5 A at 24 V AC 50/60 Hz AC-15: 5 A at 24 V AC 50/60 Hz AC-15: 5 A at 24 V AC 50/60 Hz DC-12: 0.2 A at 250 V DC DC-12: 0.2 A at 125 V DC DC-12: 2.5 A at 48 V DC DC-12: 4 A at 24 V DC DC-14: 0.2 A at 250 V DC
	DC-14: 1 A at 48 V DC DC-14: 3 A at 24 V DC
Minimum load	10 mA at 24 V
Auxiliary connection terminal	Lead wire

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7 cm
Package 1 Width	2.5 cm
Package 1 Length	8 cm
Package 1 Weight	39 g

Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Height	8 cm
Package 2 Width	9 cm
Package 2 Length	14 cm
Package 2 Weight	254 g
Unit Type of Package 3	S03
Number of Units in Package 3	120
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	6.631 kg

Offer Sustainability

REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
China RoHS Regulation	China RoHS declaration	
RoHS exemption information	Yes	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

Contractual warranty

Warranty 18 months

Recommended replacement(s)