

CA-19P1N1280DN - Cable connector



1619751

<https://www.phoenixcontact.com/in/products/1619751>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



M23, Cable connector, CA, straight, shielded: yes, Screw locking, No. of pos.: 16+3, Direction of rotation: Standard, type of contact: Pin, Solder connection, cable diameter range: 3 mm ... 14.5 mm, coding:N, Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1243803

Your advantages

- Safe use in the field, thanks to high degree of protection
- Connector for flexible on-site assembly
- Consistent EMC protection for reliable transmission of signals
- Solder connection: proven connection technology for various litz wires

Commercial Data

Item number	1619751
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	ABR
Product Key	ABRBFA
Catalog Page	Page 87 (C-2-2019)
GTIN	4046356821667
Weight per Piece (including packing)	97.8 g
Weight per Piece (excluding packing)	95.2 g
Customs tariff number	85366990
Country of origin	DE

CA-19P1N1280DN - Cable connector



1619751

<https://www.phoenixcontact.com/in/products/1619751>

Technical Data

Product properties

Product type	Circular connector (cable-side)
--------------	---------------------------------

Connector

Insulating body

Coding	N
Insulation body material	PA 6.6
Contact material	CuZn
Contact surface material	Ni/Au
Insertion/withdrawal cycles	100
Connection method	Solder connection
Contact type	Pin
Application	Signal
Number of positions	19
Direction of rotation	Standard
Connection profile	16+3
Contact diameter Power contacts	1.5 mm
Litz wire cross-section Power contacts max.	1 mm ²
Rated current Power contacts	10 A
Rated voltage	48 V AC 74 V DC
Rated surge voltage	1.5 kV
Overvoltage category	III
Degree of pollution	3
Contact diameter Signal contacts	1 mm
Litz wire cross-section Signal contacts max.	1 mm ²
Nominal current per signal contact	8 A
Installation height	2000 m

Housing

Housing material	Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)
Type of locking	Screw locking
Pg screw connection	none
Degree of protection (plugged in)	IP67
Thread type	M23

Seal

External cable diameter	3 mm ... 14.5 mm
Seal material	NBR

CA-19P1N1280DN - Cable connector



1619751

<https://www.phoenixcontact.com/in/products/1619751>

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)

-40 °C ... 125 °C

CA-19P1N1280DN - Cable connector




1619751

<https://www.phoenixcontact.com/in/products/1619751>

Drawings

Schematic diagram




CA-19P1N1280DN - Cable connector



1619751

<https://www.phoenixcontact.com/in/products/1619751>

Dimensional drawing




CA-19P1N1280DN - Cable connector




1619751

<https://www.phoenixcontact.com/in/products/1619751>

Approvals

 cUL Recognized Approval ID: E335019-20141210				
	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
	48 V	6 A	- 18	-
	48 V	5 A	- 18	-

 UL Recognized Approval ID: E335019-20141210				
	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
	48 V	10 A	- 18	-
	48 V	8 A	- 18	-

CA-19P1N1280DN - Cable connector



1619751

<https://www.phoenixcontact.com/in/products/1619751>

Classifications

ECLASS

ECLASS-11.0	27440102
ECLASS-12.0	27440116
ECLASS-13.0	27440116

ETIM

ETIM 8.0	EC002635
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

CA-19P1N1280DN - Cable connector



1619751

<https://www.phoenixcontact.com/in/products/1619751>

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

CA-19P1N1280DN - Cable connector

1619751

<https://www.phoenixcontact.com/in/products/1619751>

Accessories

SF-Z0028 - Torque screwdriver

1607456

<https://www.phoenixcontact.com/in/products/1607456>

Torque screwdriver, series: RC



SF-Z0027 - Hook wrench

1607455

<https://www.phoenixcontact.com/in/products/1607455>

Hook wrench, series: RC



CA-19P1N1280DN - Cable connector

1619751

<https://www.phoenixcontact.com/in/products/1619751>

RC-Z2058 - Protective cap

1604223

<https://www.phoenixcontact.com/in/products/1604223>

Plastic protection cap for connectors with M23 knurled nut



RC-Z2468 - Protective cap

1611796

<https://www.phoenixcontact.com/in/products/1611796>

Plastic protection cap, antistatic, for connectors with M23 knurled nut



CA-19P1N1280DN - Cable connector



1619751

<https://www.phoenixcontact.com/in/products/1619751>

RF-Z0014 - Color-coding

1620588

<https://www.phoenixcontact.com/in/products/1620588>

Color-coding, color: green



RF-Z0015 - Color-coding

1620592

<https://www.phoenixcontact.com/in/products/1620592>

Color-coding, color: orange



CA-19P1N1280DN - Cable connector

1619751

<https://www.phoenixcontact.com/in/products/1619751>



RF-Z0016 - Color-coding

1620593

<https://www.phoenixcontact.com/in/products/1620593>

Color-coding, color: black



RF-Z0003 - Square mounting flange

1607905

<https://www.phoenixcontact.com/in/products/1607905>



Square mounting flange, Axial seal, 4xM3, flange dimensions: 35 mm x 35 mm, series: RF, Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1242369

CA-19P1N1280DN - Cable connector

1619751

<https://www.phoenixcontact.com/in/products/1619751>



CA-Z0077 - Metal protective cap

1627224

<https://www.phoenixcontact.com/in/products/1627224>



Metal protective cap, degree of protection: IP67, Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1245447

RF-Z0007 - Special wrench

1614347

<https://www.phoenixcontact.com/in/products/1614347>

Special wrench, series: RF



Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.
A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420
info@phoenixcontact.co.in