



Main information

Offer	Harmony XB2
Material	Plastic
Function	Buzzer
Installation diameter	22 mm

Additional information

Rated voltage [Us]	24 V +/- 10 %
Input type	AC/DC
Power frequency	50/60 Hz
Current consumption	<20 mA
Sound type	Intermittent tone

Environment

Noise level	85 dB
Storage temperature	-40...70 °C
Operating temperature	-25...70 °C
Overvoltage type	Class II / IEC 60536
Ingression protection level	IP40 / IEC 60529
Shock protection level	IK03 / EN 50102
Standards	EN 60947-5-1 IEC 60947-1 EN 60947-5-4 EN 60947-1 IEC 60947-5-4

Packaging

Weight of package 1	22.800 g
Package 1 height	1.000 cm
Package 1 width	1.000 cm
Package 1 length	1.000 cm

Sustainability

Type	Green Premium
REACH (no SVHC)	Yes
EU ROHS Directive	Active compliance (products beyond the legal scope of EU RoHS) EU ROHS statement
Mercury free	Yes
RoHS exemption information	Yes
China ROHS	China ROHS statement
Environmental disclosure	Product environmental documents
End of life	Product end of life information
WEEE	The product must be disposed of in the EU market after specific waste recycling treatment and must not be discarded in the trash can.

Contract warranty

Warranty	18 months
----------	-----------

