

# Product datasheet

Specifications



## Acti 9 - fuse-disconnector STI - 3 poles - 25 A - for fuse 10.3 x 38 mm

A9N15656

### Main

|                           |                   |
|---------------------------|-------------------|
| Range                     | Acti9             |
| Product name              | Acti9 STI         |
| Product or component type | Fuse-disconnector |
| Device short name         | STI               |
| Poles description         | 3P                |

### Complementary

|                                |   |
|--------------------------------|---|
| [In] rated current             | 2 A<br>4 A<br>6 A<br>10 A<br>16 A<br>20 A<br>25 A   |
| Fuse curve                     | GG<br>AM  |
| Fuse size                      | 10.3 x 38 mm  |
| [Ue] rated operational voltage | 500 V AC  |
| [Ui] rated insulation voltage  | 500 V AC 50/60 Hz   |
| Mounting mode                  | Clip-on   |
| Mounting support               | DIN rail  |
| 9 mm pitches                   | 6   |
| Height                         | 81 mm   |
| Width                          | 54 mm   |
| Depth                          | 75 mm   |
| Colour                         | White   |
| Connections - terminals        | Screw clamp terminals1 cable(s) 0.75...10 mm <sup>2</sup> rigid<br>Screw clamp terminals1 cable(s) 0.5...6 mm <sup>2</sup> flexible<br>Screw clamp terminals2 cable(s) 0.75...4 mm <sup>2</sup> rigid<br>Screw clamp terminals2 cable(s) 0.5...6 mm <sup>2</sup> flexible |
| Wire stripping length          | 12 mm   |
| Tightening torque              | 2 N.m   |

### Environment

|           |                |
|-----------|----------------|
| Standards | IEC EN 60947-3 |
|-----------|----------------|

|                                       |             |
|---------------------------------------|-------------|
| IP degree of protection               | IP20        |
| Pollution degree                      | 3           |
| Ambient air temperature for operation | -20...60 °C |
| Ambient air temperature for storage   | -40...80 °C |

## Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 5.500 cm  |
| Package 1 Width              | 7.500 cm  |
| Package 1 Length             | 8.500 cm  |
| Package 1 Weight             | 165.800 g |
| Unit Type of Package 2       | BB1       |
| Number of Units in Package 2 | 4         |
| Package 2 Height             | 8.500 cm  |
| Package 2 Width              | 9.500 cm  |
| Package 2 Length             | 22.500 cm |
| Package 2 Weight             | 709.000 g |
| Unit Type of Package 3       | S03       |
| Number of Units in Package 3 | 48        |
| Package 3 Height             | 30.000 cm |
| Package 3 Width              | 30.000 cm |
| Package 3 Length             | 40.000 cm |
| Package 3 Weight             | 8.925 kg  |

## Offer Sustainability

|                             |   |
|-----------------------------|---|
| Sustainable offer status    | Green Premium product   |
| REACH Regulation            | <a href="#">REACH Declaration</a>   |
| REACH free of SVHC          | Yes   |
| EU RoHS Directive           | Compliant<br><a href="#">EU RoHS Declaration</a>  |
| Toxic heavy metal free      | Yes   |
| Mercury free                | Yes   |
| China RoHS Regulation       | <a href="#">China RoHS declaration</a><br>Pro-active China RoHS declaration (out of China RoHS legal scope)                 |
| RoHS exemption information  | <a href="#">Yes</a>   |
| Environmental Disclosure    | <a href="#">Product Environmental Profile</a>   |
| WEEE                        | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Halogen content performance | Halogen free product  |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 12 months |
|----------|-----------|

**Recommended replacement(s)**