

WP-G HF IP66 M40 BK - Screw connection



3240901

<https://www.phoenixcontact.com/in/products/3240901>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

Cable gland, metric thread, IP66 protection, straight



Commercial Data

Item number	3240901
Packing unit	25 pc
Minimum order quantity	25 pc
Sales Key	BF7
Product Key	BF7DSA
Catalog Page	Page 587 (C-3-2019)
GTIN	4046356710084
Weight per Piece (including packing)	33.5 g
Weight per Piece (excluding packing)	31.312 g
Customs tariff number	39174000
Country of origin	DE

3240901

<https://www.phoenixcontact.com/in/products/3240901>

Technical Data

Product properties

Product type	Corrugated pipe screw connection
Application	Cable gland
Type of the screw connection	Conduit adapter
Type	Outer thread
Cable outlet	straight
Thread type	metric

Dimensions

Width	52 mm
Height	53.5 mm

External dimensions

Outside diameter	36 mm
------------------	-------

Material specifications

Color	black
Material	PA 6
Flammability rating according to UL 94	V0
Material for screw connection	PA
Components	free from silicone, halogen, and cadmium

Cable/line

Halogen-free	yes
--------------	-----

Mechanical properties

Mechanical data

Type of the screw connection	Conduit adapter
------------------------------	-----------------

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP66
Ambient temperature (operation)	-40 °C ... 120 °C

Mounting

Wrench size	48 mm
-------------	-------

WP-G HF IP66 M40 BK - Screw connection



3240901

<https://www.phoenixcontact.com/in/products/3240901>

Approvals



UL Recognized



LR



VDE Zeichengenehmigung

WP-G HF IP66 M40 BK - Screw connection



3240901

<https://www.phoenixcontact.com/in/products/3240901>

Classifications

ECLASS

ECLASS-11.0	27430311
ECLASS-12.0	27430311
ECLASS-12.0	27430311

ETIM

ETIM 8.0	EC001469
----------	----------

UNSPSC

UNSPSC 21.0	39121300
-------------	----------

WP-G HF IP66 M40 BK - Screw connection



3240901

<https://www.phoenixcontact.com/in/products/3240901>

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

WP-G HF IP66 M40 BK - Screw connection

3240901

<https://www.phoenixcontact.com/in/products/3240901>

Accessories

WP-PA HF 42,5 BK - Protective hose

3241089

<https://www.phoenixcontact.com/in/products/3241089>



Protective hose, material: PA 6, UV-resistant: yes, flexible, degree of protection: IP68, color: black, flammability rating in acc. with UL 94: V0, inner diameter: 36 mm, Total length: 25 m

WP-PA HF-HB 42,5 BK - Protective hose

3240844

<https://www.phoenixcontact.com/in/products/3240844>



Protective hose, material: PA 6, UV-resistant: yes, flexible, degree of protection: IP68, color: black, flammability rating in acc. with UL 94: HB, inner diameter: 36 mm, Total length: 25 m

WP-G HF IP66 M40 BK - Screw connection

3240901

<https://www.phoenixcontact.com/in/products/3240901>

WP-BASE A M40 - Protective hose fixing bracket

3241087

<https://www.phoenixcontact.com/in/products/3241087>



Fixing bracket for protective sleeves, fixed with two screws

WP-OR M40 - Sealing ring

3241193

<https://www.phoenixcontact.com/in/products/3241193>



Sealing ring, for threads M40, color: black

WP-G HF IP66 M40 BK - Screw connection



3240901

<https://www.phoenixcontact.com/in/products/3240901>

A-INL-M40-P-BK - Counter nut

1411218

<https://www.phoenixcontact.com/in/products/1411218>

Counter nut, for threads M40 x 1.5, color: jet black



Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.

A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420

info@phoenixcontact.co.in