

# TB 6 EI - Feed-through terminal block



3246036

<https://www.phoenixcontact.com/in/products/3246036>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Feed-through terminal block, nom. voltage: 1000 V, nominal current: 41 A, number of connections: 2, connection method: Screw connection, cross section: 1.5 mm<sup>2</sup> - 6 mm<sup>2</sup>, mounting type: NS 35/7,5, NS 35/15, NS 32, color: dark gray

## Commercial Data

Item number	3246036
Packing unit	50 pc
Minimum order quantity	50 pc
Sales Key	BE1
Product Key	BE1411
GTIN	4046356599870
Weight per Piece (including packing)	12.601 g
Weight per Piece (excluding packing)	12.601 g
Customs tariff number	85369010
Country of origin	IN

# TB 6 EI - Feed-through terminal block



3246036

<https://www.phoenixcontact.com/in/products/3246036>

## Technical Data

### Product properties

Product type	Feed-through terminal block
Number of connections	2
Number of rows	1
Potentials	1

### Insulation characteristics

Overvoltage category	III
Degree of pollution	3

### Electrical properties

Rated surge voltage	8 kV
Maximum power dissipation for nominal condition	1.31 W

### Connection data

Number of connections per level	2
Nominal cross section	6 mm <sup>2</sup>

### Level 1 above 1 below 1

Screw thread	M3,5
Tightening torque	1 Nm
Stripping length	10 mm
Internal cylindrical gage	A5
Connection in acc. with standard	IEC 60947-7-1
Conductor cross section rigid	1.5 mm <sup>2</sup> ... 6 mm <sup>2</sup>
Cross section AWG	16 ... 8 (converted acc. to IEC)
Conductor cross section flexible	1.5 mm <sup>2</sup> ... 6 mm <sup>2</sup>
Conductor cross section, flexible [AWG]	16 ... 8 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve)	1.5 mm <sup>2</sup> ... 6 mm <sup>2</sup>
Flexible conductor cross section (ferrule with plastic sleeve)	1.5 mm <sup>2</sup> ... 6 mm <sup>2</sup>
2 conductors with same cross section, solid	1.5 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
2 conductors with the same cross-section AWG rigid	16 ... 14 (converted acc. to IEC)
2 conductors with same cross section, flexible	1.5 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
2 conductors with the same cross-section AWG flexible	16 ... 14 (converted acc. to IEC)
2 conductors with same cross section, flexible, with ferrule without plastic sleeve	1.5 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>
Nominal current	41 A
Maximum load current	41 A
Nominal voltage	1000 V (in the case of enclosed clamping space)

### Dimensions

Width	8.2 mm
End cover width	1.8 mm

# TB 6 EI - Feed-through terminal block



3246036

<https://www.phoenixcontact.com/in/products/3246036>

Height NS 35/15	54.7 mm
Height NS 35/7,5	47.2 mm
Height	1.85 "
Height NS 32	52 mm
Length	42.5 mm

## Material specifications

Color	dark gray
Flammability rating according to UL 94	V2
Insulating material group	I
Insulating material	PA
Static insulating material application in cold	-40 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	125 °C
Relative insulation material temperature index (Elec., UL 746 B)	125 °C

## Electrical tests

### Surge voltage test

Test voltage setpoint	9.8 kV
Result	Test passed

### Temperature-rise test

Requirement temperature-rise test	Increase in temperature $\leq 45$ K
Result	Test passed
Result	Test passed

### Power-frequency withstand voltage

Test voltage setpoint	2.2 kV
Result	Test passed

## Mechanical properties

### Mechanical data

Open side panel	Yes
-----------------	-----

## Mechanical tests

### Mechanical strength

Result	Test passed
--------	-------------

### Attachment on the carrier

DIN rail/fixing support	NS 32/NS 35
Result	Test passed

### Test for conductor damage and slackening

Rotation speed	10 rpm
Revolutions	135

# TB 6 EI - Feed-through terminal block



3246036

<https://www.phoenixcontact.com/in/products/3246036>

Conductor cross section/weight	1.5 mm <sup>2</sup> / 0.4 kg
	6 mm <sup>2</sup> / 1.4 kg
Result	Test passed

## Environmental and real-life conditions

### Needle-flame test

Time of exposure	30 s
Result	Test passed

### Oscillation/broadband noise

Specification	DIN EN 50155 (VDE 0115-200):2018-05
Spectrum	Service life test category 2, bogie-mounted
Frequency	$f_1 = 5 \text{ Hz}$ to $f_2 = 250 \text{ Hz}$
ASD level	6.12 (m/s <sup>2</sup> ) <sup>2</sup> /Hz
Acceleration	3.12g
Test duration per axis	5 h
Test directions	X-, Y- and Z-axis
Result	Test passed

### Shocks

Pulse shape	Half-sine
Acceleration	30g
Shock duration	18 ms
Number of shocks per direction	3
Test directions	X-, Y- and Z-axis (pos. and neg.)
Result	Test passed

### Ambient conditions

Ambient temperature (operation)	-60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (storage/transport)	30 % ... 70 %

## Standards and regulations

Connection in acc. with standard	IEC 60947-7-1
----------------------------------	---------------

## Mounting

Mounting type	NS 35/7,5
	NS 35/15
	NS 32

# TB 6 EI - Feed-through terminal block

3246036

<https://www.phoenixcontact.com/in/products/3246036>



## Drawings

### Circuit diagram




# TB 6 EI - Feed-through terminal block



3246036

<https://www.phoenixcontact.com/in/products/3246036>

## Approvals

 <b>UL Recognized</b> Approval ID: E60425				
	Nominal Voltage $U_N$	Nominal Current $I_N$	Cross Section AWG	Cross Section $\text{mm}^2$
	600 V	45 A	16 - 8	-
	600 V	45 A	16 - 8	-
	600 V	45 A	16 - 8	-
	600 V	5 A	16 - 8	-

# TB 6 EI - Feed-through terminal block



3246036

<https://www.phoenixcontact.com/in/products/3246036>

## Classifications

### ECLASS

ECLASS-11.0

27141120

### ETIM

ETIM 7.0

EC000897

### UNSPSC

UNSPSC 21.0

39121410

# TB 6 EI - Feed-through terminal block



3246036

<https://www.phoenixcontact.com/in/products/3246036>

## Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values



# TB 6 EI - Feed-through terminal block

3246036

<https://www.phoenixcontact.com/in/products/3246036>



## Accessories

### SCBI 10-8 - Fixed bridge

3246133

<https://www.phoenixcontact.com/in/products/3246133>

Fixed bridge, number of positions: 10, color: silver



---

### INB 10-8 - Insertion bridge

3246191

<https://www.phoenixcontact.com/in/products/3246191>

Insertion bridge, Bridging in the terminal point, pitch: 8 mm, number of positions: 10, color: gray



# TB 6 EI - Feed-through terminal block

3246036

<https://www.phoenixcontact.com/in/products/3246036>



## D-TB 4/10 E - End cover

3246104

<https://www.phoenixcontact.com/in/products/3246104>

End cover, length: 42.5 mm, width: 1.5 mm, height: 35.9 mm, color: dark gray



---

## TS-TB - Separating plate

3062838

<https://www.phoenixcontact.com/in/products/3062838>

Separating plate, for electrical isolation of neighboring bridges in the terminal center, length: 22 mm, height: 22 mm, color: dark gray



# TB 6 EI - Feed-through terminal block

3246036

<https://www.phoenixcontact.com/in/products/3246036>



## ATP-TB - Partition plate

3046272

<https://www.phoenixcontact.com/in/products/3046272>



Partition plate, length: 56 mm, width: 3 mm, height: 45.7 mm, color: dark gray

---

## TPS 4/7/6 - Female test connector

3246243

<https://www.phoenixcontact.com/in/products/3246243>



Female test connector, for 4 mm test plugs, for screwing into the bridge shaft, number of positions: 1, fuse type: , mounting type: , , color: silver

# TB 6 EI - Feed-through terminal block

3246036

<https://www.phoenixcontact.com/in/products/3246036>



## SZS 1,0X4,0 VDE - Screwdriver

1205066

<https://www.phoenixcontact.com/in/products/1205066>



Screwdriver, slot-headed, VDE insulated, size: 1.0 x 4.0 x 100 mm, 2-component grip, with non-slip grip

---

## E/TB - End clamp

3246966

<https://www.phoenixcontact.com/in/products/3246966>



End clamp, for assembly on NS 32 or NS 35/7.5 DIN rail

# TB 6 EI - Feed-through terminal block

3246036

<https://www.phoenixcontact.com/in/products/3246036>



## NS 32 PERF 2000MM-VPE 10 - DIN rail perforated

1201002

<https://www.phoenixcontact.com/in/products/1201002>



DIN rail perforated, acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, G profile, color: silver, Pack of 10 (20 m)

---

## NS 32 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201015

<https://www.phoenixcontact.com/in/products/1201015>



DIN rail, unperforated, acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, G profile, color: silver, Pack of 10 (20 m)

# TB 6 EI - Feed-through terminal block

3246036

<https://www.phoenixcontact.com/in/products/3246036>



## PS-MT - Test plugs

0311647

<https://www.phoenixcontact.com/in/products/0311647>



Test plugs, number of positions: 1, fuse type: , mounting type: , , color: silver

---

## PS-IH WH - Insulating sleeve

0311566

<https://www.phoenixcontact.com/in/products/0311566>



Insulating sleeve, number of positions: 1, fuse type: , mounting type: , , color: white

# TB 6 EI - Feed-through terminal block

3246036

<https://www.phoenixcontact.com/in/products/3246036>



## PS-IH RD - Insulating sleeve

0311579

<https://www.phoenixcontact.com/in/products/0311579>



Insulating sleeve, number of positions: 1, fuse type: , mounting type: , , color: red

---

## PS-IH BU - Insulating sleeve

0311582

<https://www.phoenixcontact.com/in/products/0311582>



Insulating sleeve, number of positions: 1, fuse type: , mounting type: , , color: blue

# TB 6 EI - Feed-through terminal block

3246036

<https://www.phoenixcontact.com/in/products/3246036>



## PS-IH YE - Insulating sleeve

0311595

<https://www.phoenixcontact.com/in/products/0311595>



Insulating sleeve, number of positions: 1, fuse type: , mounting type: , , color: yellow

---

## PS-IH GN - Insulating sleeve

0311605

<https://www.phoenixcontact.com/in/products/0311605>



Insulating sleeve, number of positions: 1, fuse type: , mounting type: , , color: green



# TB 6 EI - Feed-through terminal block

3246036

<https://www.phoenixcontact.com/in/products/3246036>



## PS-IH GY - Insulating sleeve

0311621

<https://www.phoenixcontact.com/in/products/0311621>



Insulating sleeve, number of positions: 1, fuse type: , mounting type: , , color: gray

---

## PS-IH BK - Insulating sleeve

0311634

<https://www.phoenixcontact.com/in/products/0311634>



Insulating sleeve, number of positions: 1, fuse type: , mounting type: , , color: black

# TB 6 EI - Feed-through terminal block

3246036

<https://www.phoenixcontact.com/in/products/3246036>



## PS-IH VT - Insulating sleeve

0311618

<https://www.phoenixcontact.com/in/products/0311618>



Insulating sleeve, number of positions: 1, fuse type: , mounting type: , , color: violet

---

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.

A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420

[info@phoenixcontact.co.in](mailto:info@phoenixcontact.co.in)