

# VAL-MB-T1/T2 1500DC-PV/2+V-FM - Lightning/surge arrester type 1/2



2905640

<https://www.phoenixcontact.com/in/products/2905640>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Lightning current arrester/surge protective device for 2-pos. isolated and grounded 1,500 V DC PV systems, for DIN rail mounting, with remote indication contact, temperature-monitored protective elements, status message on the module.

## Your advantages

- Space-saving installation, thanks to the compact design
- Double terminal block for safe and easy equipotential bonding connection
- Screw shafts with raised domes to ensure safe working
- Main connections with extended insertion funnels for increased resistance to creepage
- Visual display for checking the status directly on the device
- Plug-in signal connection for remote status signaling

## Commercial Data

Item number	2905640
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	CL1
Product Key	CL1231
Catalog Page	Page 51 (C-4-2019)
GTIN	4046356984423
Weight per Piece (including packing)	531.1 g
Weight per Piece (excluding packing)	531.1 g
Customs tariff number	85354000
Country of origin	DE

# VAL-MB-T1/T2 1500DC-PV/2+V-FM - Lightning/surge arrester type 1/2



2905640

<https://www.phoenixcontact.com/in/products/2905640>

## Technical Data

### Notes

#### General

Note	The product is also suitable for use in photovoltaic systems with max. short-circuit current $I_{SCPV} = 15 \text{ kA}$ (in accordance with EN 50539-11: 2013).
------	---

### Product properties

IEC test classification	PV I / II PV T1 / T2
EN type	T1 / T2
IEC power supply system	DC
Type	DIN rail module, one-piece
Product type	PV arrester
Product family	VALVETRAB MB
Installation location	Interior
Installation location of the disconnect device	Internal
Accessibility	Accessible
Connection configuration	Y configuration
SPD failure behavior	OCFM (Open-Circuit Failure Mode)
Surge protection fault message	Optical, remote indicator contact

#### Insulation characteristics

Pollution degree	2
------------------	---

### Electrical properties

#### Indicator/remote signaling

Connection name	Remote fault indicator contact
Switching function	Changeover contact
Operating voltage	5 V AC ... 250 V AC 5 V DC ... 30 V DC
Operating current	5 mA AC ... 1.5 A AC 5 mA DC ... 1 A DC

### Connection data

Connection method	Screw connection
Screw thread	M5
Tightening torque	3 Nm
Stripping length	16 mm
Conductor cross section flexible	2.5 mm <sup>2</sup> ... 35 mm <sup>2</sup>
Conductor cross section AWG	14 ... 2

# VAL-MB-T1/T2 1500DC-PV/2+V-FM - Lightning/surge arrester type 1/2


2905640

<https://www.phoenixcontact.com/in/products/2905640>

## Remote fault indicator contact

Connection method	Screw connection
Screw thread	M2
Tightening torque	0.25 Nm
Conductor cross section flexible	0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>
Conductor cross section rigid	0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>
Conductor cross section AWG	28 ... 16

## Dimensions

Dimensional drawing	
Width	71.2 mm
Height	120 mm
Depth	65.5 mm (incl. DIN rail 7.5 mm)
Horizontal pitch	4 Div.

## Material specifications

Color	traffic grey A RAL 7042
Flammability rating according to UL 94	V-0
Insulating material	PA 6.6 PBT
Housing material	PA 6.6

## Mechanical properties

### Mechanical data

Open side panel	No
-----------------	----

## Protective circuit

Mode of protection	(L+) - (L-) (L+) - PE (L-) - PE
Direction of action	(L+)-PE & (L-)-PE & (L+)-(L-)
Rated load current $I_L$	50 A
Residual current $I_{PE}$	$\leq 100 \mu\text{A DC}$ $\leq 540 \mu\text{A AC}$
Standby power consumption $P_C$	$\leq 150 \text{ mVA}$
Nominal discharge current $I_n$ (8/20) $\mu\text{s}$	20 kA
Maximum discharge current $I_{max}$ (8/20) $\mu\text{s}$	40 kA
Impulse discharge current (10/350) $\mu\text{s}$ , charge	3.125 As
Impulse discharge current (10/350) $\mu\text{s}$ , specific energy	9.77 kJ/ $\Omega$

# VAL-MB-T1/T2 1500DC-PV/2+V-FM - Lightning/surge arrester type 1/2



2905640

<https://www.phoenixcontact.com/in/products/2905640>

Impulse discharge current (10/350) $\mu\text{s}$ , peak value $I_{\text{imp}}$	6.25 kA
Total discharge current $I_{\text{total}}$ (8/20) $\mu\text{s}$	40 kA
Total discharge current $I_{\text{total}}$ (10/350) $\mu\text{s}$	12.5 kA
Voltage protection level $U_p$	$\leq 4.5$ kV
Residual voltage $U_{\text{res}}$	$\leq 4.5$ kV (at $I_n$ )
	$\leq 3.3$ kV (at 3 kA)
	$\leq 3.6$ kV (at 6.25 kA)
	$\leq 3.8$ kV (at 10 kA)
	$\leq 4.2$ kV (at 15 kA)
	$\leq 5.4$ kV (at 40 kA)
Response time $t_A$	$\leq 25$ ns

## PV protective circuit

Connection configuration	Y configuration
SPD failure behavior	OCFM (Open-Circuit Failure Mode)

## Protective circuit DC voltage side (DC)

Open circuit voltage $U_{\text{OCSTC}}$	$\leq 1250$ V DC
Maximum discharge current $I_{\text{max}}$ (8/20) $\mu\text{s}$	40 kA
Response time $t_A$	$\leq 25$ ns
Impulse discharge current (10/350) $\mu\text{s}$ , charge	3.125 As
Impulse discharge current (10/350) $\mu\text{s}$ , specific energy	9.77 kJ/ $\Omega$
Impulse discharge current (10/350) $\mu\text{s}$ , peak value $I_{\text{imp}}$	6.25 kA
Total discharge current $I_{\text{total}}$ (8/20) $\mu\text{s}$	40 kA
Total discharge current $I_{\text{total}}$ (10/350) $\mu\text{s}$	12.5 kA
Insulation resistance $R_{\text{iso}}$	$> 5$ G $\Omega$ (at 500 V DC)
Nominal discharge current $I_n$ (8/20) $\mu\text{s}$	20 kA
Rated load current $I_L$	50 A
Continuous operating current $I_{\text{CPV}}$	$< 100$ $\mu\text{A}$
Maximum continuous operating voltage $U_{\text{CPV}}$	1500 V DC
Short-circuit current rating $I_{\text{SCPV}}$	2000 A
Residual voltage $U_{\text{res}}$	$\leq 4.5$ kV (at $I_n$ )
	$\leq 3.3$ kV (at 3 kA)
	$\leq 3.6$ kV (at 6.25 kA)
	$\leq 3.8$ kV (at 10 kA)
	$\leq 4.2$ kV (at 15 kA)
	$\leq 5.4$ kV (at 40 kA)
Residual current $I_{\text{PE}}$	$\leq 100$ $\mu\text{A}$ DC
	$\leq 540$ $\mu\text{A}$ AC
Voltage protection level $U_p$	$\leq 4.5$ kV
Standby power consumption $P_C$	$\leq 150$ mVA

## Environmental and real-life conditions

# VAL-MB-T1/T2 1500DC-PV/2+V-FM - Lightning/surge arrester type 1/2



2905640

<https://www.phoenixcontact.com/in/products/2905640>

## Ambient conditions

Degree of protection	IP20 (only when all terminal points are used)
Ambient temperature (operation)	-40 °C ... 80 °C
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Altitude	≤ 6000 m (amsl (above mean sea level))
Permissible humidity (operation)	5 % ... 95 %
Shock (operation)	50g (Half-sine / 11 ms / 3x ±X, ±Y, ±Z)
Vibration (operation)	5g (5 - 500 Hz/2.5 h/X, Y, Z)

## Standards and regulations

Standards/specifications	EN 61643-31
Standards/specifications	IEC 61643-31

## Mounting

Mounting type	DIN rail: 35 mm
---------------	-----------------

# VAL-MB-T1/T2 1500DC-PV/2+V-FM - Lightning/surge arrester type 1/2




2905640

<https://www.phoenixcontact.com/in/products/2905640>

## Drawings

Dimensional drawing




# VAL-MB-T1/T2 1500DC-PV/2+V-FM - Lightning/surge arrester type 1/2

2905640

<https://www.phoenixcontact.com/in/products/2905640>

Circuit diagram



# VAL-MB-T1/T2 1500DC-PV/2+V-FM - Lightning/surge arrester type 1/2



2905640

<https://www.phoenixcontact.com/in/products/2905640>

## Approvals



**IECEE CB Scheme**  
Approval ID: NL-81007



**KEMA-KEUR**  
Approval ID: 71-127691



# VAL-MB-T1/T2 1500DC-PV/2+V-FM - Lightning/surge arrester type 1/2



2905640

<https://www.phoenixcontact.com/in/products/2905640>

## Classifications

### ECLASS

ECLASS-11.0	27130802
-------------	----------

### ETIM

ETIM 8.0	EC000381
----------	----------

### UNSPSC

UNSPSC 21.0	39121600
-------------	----------

# VAL-MB-T1/T2 1500DC-PV/2+V-FM - Lightning/surge arrester type 1/2



2905640

<https://www.phoenixcontact.com/in/products/2905640>

## Environmental Product Compliance

China RoHS

Environmentally Friendly Use Period = 50 years

For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

# VAL-MB-T1/T2 1500DC-PV/2+V-FM - Lightning/surge arrester type 1/2



2905640

<https://www.phoenixcontact.com/in/products/2905640>

## Accessories

### X-PEN 0,35 - Marker pen

0811228

<https://www.phoenixcontact.com/in/products/0811228>



Marker pen without ink cartridge, for manual labeling of markers, labeling extremely wipe-proof, line thickness 0.35 mm

### ATP-QTTCB - Partition plate

3206238

<https://www.phoenixcontact.com/in/products/3206238>

Partition plate, length: 102 mm, width: 2 mm, height: 54 mm, color: gray



Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.

A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420

[info@phoenixcontact.co.in](mailto:info@phoenixcontact.co.in)