

Product data sheet

Specifications



Auxiliary contact block, TeSys Deca, 2NO+2NC, front mounting, lugs-ring terminals

LADN226

Main

| | |
|---|--|
| Range | TeSys TeSys Deca |
| Product name | TeSys Deca |
| Product or component type | Auxiliary contact block |
| Device short name | LADN |
| Range compatibility | TeSys D CAD TeSys D LC1D TeSys F LC1F TeSys F CR1F TeSys Deca CAD TeSys Deca LC1D |
| Mounting location | Front |
| Pole contact composition | 2 NO + 2 NC |
| Contacts operation | Instantaneous |
| [Ue] rated operational voltage | 690 V AC 25...400 Hz |
| [Ie] rated operational current | 6 A at 120 V AC-15 1.04 A at 690 V AC-15 0.55 A at 125 V DC-13 0.1 A at 600 V DC-13 |
| [Ui] rated insulation voltage | 690 V conforming to IEC 60947-5-1 600 V conforming to UL 600 V conforming to CSA |
| [Ith] conventional free air thermal current | 10 A (at 60 °C) |
| Standards | EN/IEC 60947-5-1 UL 60947-5-1 CSA C22.2 No 60947-5-1 GB/T 14048.5 EN 50012 |
| Product certifications | CB UL CSA CCC EAC UKCA |

Complementary

| | |
|-------------------------------|--|
| Irms rated making capacity | 140 A AC conforming to IEC 60947-5-1 250 A DC conforming to IEC 60947-5-1 |
| Permissible short-time rating | 100 A 60 °C 1 s 120 A 60 °C 500 ms 140 A 60 °C 100 ms |

| | |
|----------------------------------|--|
| Protection type | GG fuse 10 A |
| Mechanical durability | 30 Mcycles |
| Minimum switching current | 5 mA |
| Minimum switching voltage | 17 V |
| Non-overlap time | 1.5 ms on de-energisation no overlap between NC and NO contact 1.5 ms on energisation no overlap between NC and NO contact |
| Insulation resistance | > 10 MOhm |
| Connections - terminals | Lugs-ring terminals (external diameter: 8 mm) |
| Tightening torque | 1.7 N.m - cable 3.5 mm ² - with screwdriver flat Ø 6 mm M3.5 1.7 N.m - with screwdriver Philips No 2 M3.5 1.7 N.m - with screwdriver pozidriv No 2 M3.5 |
| Height | 48 mm |
| Width | 44 mm |
| Depth | 42 mm |
| Net weight | 0.05 kg |
| Colour | Dark grey |

Environment

| | |
|--|------------------------------|
| Environmental characteristic | Normal environment |
| IP degree of protection | IP20 conforming to IEC 60529 |
| Protective treatment | TH conforming to IEC 60068 |
| Ambient air temperature for storage | -60...80 °C |
| Ambient air temperature for operation | -5...60 °C |
| Operating altitude | 3000 m |

Packing Units

| | |
|-------------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 5 cm |
| Package 1 Width | 4.8 cm |
| Package 1 Length | 4 cm |
| Package 1 Weight | 58 g |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 10 |
| Package 2 Height | 5.3 cm |
| Package 2 Width | 8.3 cm |
| Package 2 Length | 25.4 cm |
| Package 2 Weight | 580 g |
| Unit Type of Package 3 | S03 |
| Number of Units in Package 3 | 160 |
| Package 3 Height | 30 cm |
| Package 3 Width | 30 cm |
| Package 3 Length | 40 cm |
| Package 3 Weight | 9.458 kg |

Offer Sustainability

| | |
|-----------------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Recommended replacement(s)