

# Product datasheet

Specifications



pilot light Ø8 - IP40 - green -  
protruding LED included -  $\leq 30$  mA  
- faston

XVLA193

! Discontinued on: 01 November 2020

! End-of-service on: 11 July 2022

! Discontinued

## Main

Range of product	Harmony XVL
Product or component type	LED pilot light with black bezel
Component name	XVL
Mounting diameter	8 mm
Light source	Protruding LED
Light block colour	Green
Protection type	Without protection
IP degree of protection	IP40 conforming to IEC 60529 IP40 conforming to NF C 20-010

## Complementary

Input current	30 mA DC
Connections - terminals	Tag for soldering connectors Tag for Faston connectors
[Ui] rated insulation voltage	50 V conforming to IEC 60947-1
Bulb lifespan	100000 h
Terminals description ISO n°1	(X1-X2)PL
Height	10 mm
Width	10 mm
Depth	36 mm
Net weight	0.003 kg

## Environment

Product certifications	CSA UL
Protective treatment	TC
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C
Overvoltage category	Class 3 conforming to IEC 60536 Class 3 conforming to NF C 20-030

### Packing Units

---

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.6 cm
Package 1 Width	1.6 cm
Package 1 Length	4 cm
Package 1 Weight	3 g

---

### Contractual warranty


---

Warranty	18 months
----------	-----------

---

**LED Pilot Light**

**Dimensions**




- (1) Tags for Faston connectors or soldered connections  
panel thickness: 1 to 8 mm/0.03 to 0.31 in.

C		Ø	
mm	in.	mm	in.
32	1.26	12	0.47

**LED Pilot Light**

**Panel Drilling**



Ø min		G min		H min	
mm	in.	mm	in.	mm	in.
8.2	0.32	12.5	0.49	12.5	0.49

**Recommended replacement(s)**

XVLA193 is replaced by the following product range:



**Harmony XVL**

Ø 8-12 mm LED plastic pilot lights

Products: 30