



**MATERIAL:**

- SEAL : FLUOROSILICONE PER SAE AMS-R-25988
- OUTER CONTACTS, CLAMP NUT, RING GLAND, SPACER AND BRAID CLAMP: BRASS PER ASTM B 16 OR ASTM B 453 OR EN 12164
- CENTER CONTACT : BERYLLIUM COPPER PER ASTM B 196
- SPRING AND FLAT WASHER : STAINLESS STEEL PER SAE AMS-5514
- INSULATOR : PTFE PER ASTM D 1710 OR EQUIVALENT
- RETAINING CLIP : CORROSION RESISTANT MATERIAL

**FINISH:**

- ALL METALLIC PARTS : PLATING .00005 INCH OF GOLD PER SAE AMS-2422 OVER NICKEL PER AMS 2403

WIRING INSTRUCTIONS : SEE MI CT 01 00023

MOUNTING ASSEMBLY : SEE MI IN 20 00000



DIMENSIONS : mm (inch are given for information only)

CREATION			
PEN: M95400047A			
NOM: K PECHEUX			
DATE: JAN 03 1996	MAR 12 09	REDRAWN - MODIFIED WIRING INSTRUCTION ADDED NOTE WITH : "WIRING INSTRUCTION MI CT 01 00023 AND MOUNTING ASSEMBLY MI IN 20 00000"	
APPR.: BALDYROU	Issue	Revisions	Name
			VALGRESY
			BROCHET
			Approved

620119100EN

RADIALL PROPRIETARY INFORMATION