

BNC-DV 75 - Connector/Adapter

2805083

<https://www.phoenixcontact.com/in/products/2805083>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



BNC connector, 2-pos., double-level, for mounting on NS 32 or NS 35/7,5, wave impedance: 75 Ω

Your advantages

- Can be labeled individually
- With isolated structure on the DIN rail
- For coaxial cables
- DIN rail-mountable and can be aligned

Commercial Data

| | |
|--------------------------------------|---------------------|
| Item number | 2805083 |
| Packing unit | 10 pc |
| Minimum order quantity | 10 pc |
| Sales Key | BE5 |
| Product Key | BE5ZWX |
| Catalog Page | Page 141 (C-6-2013) |
| GTIN | 4017918074579 |
| Weight per Piece (including packing) | 52.93 g |
| Weight per Piece (excluding packing) | 52.93 g |
| Customs tariff number | 85366910 |
| Country of origin | PL |

BNC-DV 75 - Connector/Adapter



2805083

<https://www.phoenixcontact.com/in/products/2805083>

Technical Data

Product properties

| | |
|---------------------|-----------------|
| Product type | Flange coupling |
| Number of positions | 2 |

Connection data

| | |
|-------------------|-----------------|
| Connection method | BNC 75 Ω |
|-------------------|-----------------|

Dimensions

| | |
|--------|---------|
| Width | 22 mm |
| Height | 90 mm |
| Length | 42.5 mm |

Material specifications

| | |
|--|------|
| Color | gray |
| Flammability rating according to UL 94 | V2 |
| Housing material | PA |

Protective circuit

| | |
|--|-----------------|
| Frequency range | 0 GHz ... 3 GHz |
| Voltage standing wave ratio VSWR in a 75 Ω system | < 1.1 (3 GHz) |

Environmental and real-life conditions

Ambient conditions

| | |
|--|---|
| Degree of protection | IP20 |
| Ambient temperature (operation) | -60 °C ... 105 °C (max. short-term operating temperature RTI Elec.) |
| Ambient temperature (storage/transport) | -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C) |
| Permissible humidity (storage/transport) | 30 % ... 70 % |

Mounting

| | |
|---------------|-----------|
| Mounting type | NS 35/7,5 |
|---------------|-----------|

BNC-DV 75 - Connector/Adapter

2805083

<https://www.phoenixcontact.com/in/products/2805083>



Approvals



EAC

Approval ID: RU C-DE.BL08.B.00511

BNC-DV 75 - Connector/Adapter



2805083

<https://www.phoenixcontact.com/in/products/2805083>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27141190 |
| ECLASS-12.0 | 27141190 |
| ECLASS-12.0 | 27141190 |

ETIM

| | |
|----------|----------|
| ETIM 8.0 | EC002848 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

BNC-DV 75 - Connector/Adapter



2805083

<https://www.phoenixcontact.com/in/products/2805083>

Environmental Product Compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

BNC-DV 75 - Connector/Adapter

2805083

<https://www.phoenixcontact.com/in/products/2805083>

Accessories

ZB 22 CUS - Zack marker strip

0824949

<https://www.phoenixcontact.com/in/products/0824949>



Zack marker strip, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 22 mm, lettering field size: 10.5 x 21.8 mm, Number of individual labels: 4

ZB 22:UNBEDRUCKT - Zack marker strip

0811862

<https://www.phoenixcontact.com/in/products/0811862>



Zack marker strip, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 22 mm, lettering field size: 10.5 x 21.8 mm, Number of individual labels: 4

BNC-DV 75 - Connector/Adapter

2805083

<https://www.phoenixcontact.com/in/products/2805083>



NS 35/ 7,5 PERF 2000MM - DIN rail perforated

0801733

<https://www.phoenixcontact.com/in/products/0801733>



DIN rail perforated, acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver, Pack of 25 (50 m)

NS 35/ 7,5 UNPERF 2000MM - DIN rail, unperforated

0801681

<https://www.phoenixcontact.com/in/products/0801681>



DIN rail, unperforated, acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver, Pack of 25 (50 m)

BNC-DV 75 - Connector/Adapter

2805083

<https://www.phoenixcontact.com/in/products/2805083>



NS 35/ 7,5 WH PERF 2000MM - DIN rail perforated

1204119

<https://www.phoenixcontact.com/in/products/1204119>



DIN rail perforated, acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver, Pack of 25 (50 m)

NS 35/ 7,5 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204122

<https://www.phoenixcontact.com/in/products/1204122>



DIN rail, unperforated, acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver, Pack of 10 (20 m)

BNC-DV 75 - Connector/Adapter

2805083

<https://www.phoenixcontact.com/in/products/2805083>



NS 35/ 7,5 AL UNPERF 2000MM - DIN rail, unperforated

0801704

<https://www.phoenixcontact.com/in/products/0801704>



DIN rail, unperforated, acc. to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver, Pack of 25 (50 m)

NS 35/ 7,5 ZN PERF 2000MM - DIN rail perforated

1206421

<https://www.phoenixcontact.com/in/products/1206421>



DIN rail perforated, acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver, Pack of 25 (50 m)

BNC-DV 75 - Connector/Adapter

2805083

<https://www.phoenixcontact.com/in/products/2805083>



NS 35/ 7,5 ZN UNPERF 2000MM - DIN rail, unperforated

1206434

<https://www.phoenixcontact.com/in/products/1206434>



DIN rail, unperforated, acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver, Pack of 25 (50 m)

NS 35/ 7,5 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

0801762

<https://www.phoenixcontact.com/in/products/0801762>



DIN rail, unperforated, acc. to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored, Pack of 10 (20 m)

BNC-DV 75 - Connector/Adapter

2805083

<https://www.phoenixcontact.com/in/products/2805083>



NS 35/ 7,5 CAP - End cap

1206560

<https://www.phoenixcontact.com/in/products/1206560>

DIN rail end piece, for DIN rail NS 35/7.5




E/AL-NS 35 - End clamp

1201662

<https://www.phoenixcontact.com/in/products/1201662>

End clamp, for end support of UKH 50 to UKH 240, is pushed onto DIN rail NS 35 and fixed with 2 screws, width: 10 mm, color: aluminum



Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.
A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420
info@phoenixcontact.co.in