


Series
EPX

SIZE 16 CRIMP PIN CONTACT

Issue:
Dec. 13, 2018

Page
1/1



MATERIAL : COPPER ALLOY (C97) HARDNESS IN KNOOP 120 MAX (107 HV) FOR CRIMP BARREL

FINISH : GOLD PER MIL-G-45204 TYPE I OR II GRADE C OR D CLASS 1 50 MICROINCHES OVER NICKEL PLATE PER QQ-N-290

WIRES ACCOMODATED : AWG 16-18-20
INSULATOR DIAMETER : 2,60 MAX (0,103)
STRIP LENGHT : 6 (0,236)

CRIMP CONTACT TENSILE REQUIREMENTS USING MIL SPEC TOOLING AND WIRE SPEC
MIL-W-81381/12 16 GA. 37 LBS (16,5 daN)
MIL-W-22759/41 16 GA. 50 LBS (22,5 daN)
M22520/1-01 16 GA. 49 LBS (22 daN)


CRIMPED CONTACTS WILL SHOW NO CRACK WHEN INSPECTED PER MIL-C-22520 AT 10X

RADIALL TOOLING RECOMMENDATION
CRIMPING TOOL : M22520/1-01 (RADIALL 282 291)
SELECTOR POSITION : 6 FOR AWG 16
5 FOR AWG 18
4 FOR AWG 20

POSITIONER : M22520/1-02 (RADIALL 282 972)

INSERTION/EXTRACTION TOOL : M81969/1-03 (RADIALL 282 546)
SPL RADIALL INS. 282 929 / EXT. 282 892

DIMENSIONS : mm (inch are given for information only)



Estimated weight : 0,56 g

This document contains proprietary information and such information shall not be disclosed to any third party for any purpose whatsoever or used for manufacturing purposes without prior written agreement from RADIALL. This information is given as an indication. In the continual goal to improve our products, we reserve the right to make any modifications judged necessary.

4112_9311

CREATION PEN: NOM: MACARI JP. DATE: 01 NOV 86 APPR.:				
	Dec. 13, 18	Added estimated weight	Weihs H.	Lopez C.
	Nov 28, 06	Redrawn and dimensions modified	PAILOT N	DUPUIS
	Issue	Revisions	Name	Approved