

Product datasheet

Specifications



mini Kaedra - for modular device - 1 openings - 12 modules - 2 terminal blocks

13444

Main

Range	Kaedra
Product or component type	Weatherproof enclosure
Enclosure type	Mini enclosure for modular device
Accessories included with enclosure	1 marking kit 2 terminal blocks 8 holes
Mounting plate description	Without mounting plate

Complementary

Enclosure mounting	Surface
Number of 18 mm modules per row	12
Total number of 18 mm modules	12
Number of horizontal rows	1
Electrical insulation class	Class II Double insulation
Provided equipment	1 marking kit 2 terminal block 8 holes
Type of front cover	Transparent
Power dissipation in W	19 W
[In] rated current	63 A
Type of rail	DIN
Number of pre-cutouts PG ISO	7
Number of terminal blocks	2 with 8 outgoers
Distribution block outgoers	8 x 10 mm ² 8 x 16 mm ²
Locking options description	Optional keylock
Enclosure material	Self-extinguishing polymer
Width	267 mm
Height	200 mm
Depth	112 mm
Internal depth	56 mm
Colour	Door: transparent green

Environment

Standards	EN 50262 EN 50102 IEC 60439-3 IEC 670 IEC 60529 IEC 60695-2-1
Fire resistance	650 °C conforming to IEC 60695-2-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 50102
Environmental characteristics (UV)	UV resistant: class 3 conforming to ISO 4582:2010 Ultraviolet degradation test conforming to ISO 4892-2:2013
Overvoltage category	II
Ambient air temperature for operation	-25...60 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.000 cm
Package 1 Width	20.000 cm
Package 1 Length	26.500 cm
Package 1 Weight	935.000 g
Unit Type of Package 2	CAR
Number of Units in Package 2	4
Package 2 Height	22.000 cm
Package 2 Width	35.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	4.093 kg
Unit Type of Package 3	P12
Number of Units in Package 3	96
Package 3 Height	80.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	113.280 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)

RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Halogen content performance	Halogen free product
Minimum percentage of recycled plastic content	24

Contractual warranty

Warranty	18 months
-----------------	-----------

Recommended replacement(s)