

0830927

https://www.phoenixcontact.com/in/products/0830927

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

Marker for terminal blocks, Strip, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 5 x 5 mm, Number of individual labels: 24



Your advantages

- · The markers, which are supplied in uniform strips, can be printed onto quickly and easily using the BLUEMARK printing systems
- The UM-TMF ... UM labeling range includes terminal markers for Phoenix Contact terminal blocks with flat marker groove
- · The multi-section marking strips are easy to fit and can be easily separated if required
- · The markers support multi-line labeling

Commercial Data

| Item number | 0830927 |
|--------------------------------------|---------------|
| Packing unit | 10 pc |
| Minimum order quantity | 10 pc |
| Sales Key | BG2 |
| Product Key | BG211M |
| GTIN | 4046356910620 |
| Weight per Piece (including packing) | 1.39 g |
| Weight per Piece (excluding packing) | 1.23 g |
| Customs tariff number | 39269097 |
| Country of origin | PL |



0830927

https://www.phoenixcontact.com/in/products/0830927

Technical Data

Product properties

| Product type | Terminal marking |
|-------------------------------------|----------------------------------|
| Pitch | 5.2 mm |
| Туре | flat |
| Area of application | Phoenix Contact |
| arking | |
| Number of individual labels | 24 |
| Number of individual labels per row | 12 |
| Number of marker strips | 2 |
| arking technology | |
| Device | 5146464 THERMOMARK CARD |
| | |
| Ink ribbon | 0801371 THERMOMARK-RIBBON 110-TC |

D

| Width | 5 mm |
|--------|--------|
| Length | 5 mm |
| Pitch | 5.2 mm |

Material specifications

| RoHS compliant | yes |
|--|--|
| Color | white |
| Material | PC |
| Flammability rating according to UL 94 | V2 |
| Components | free from silicone, halogen, and cadmium |

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

| Result | Test passed |
|---------------------------------|--|
| resistance | |
| Specification | ISO 4892-2:2013-03 (following) |
| Result | Test passed |
| Vipe resistance of inscriptions | |
| Specification | IEC 61010-1:2010-06 |
| | DIN EN 62208 (VDE 0660-511):2012-06 (in parts) |

Testing in a condensation changing climate in the presence of sulfur dioxide

| Specification | DIN 50018:2013-05 |
|---------------|-------------------|
| Result | Test passed |



0830927

https://www.phoenixcontact.com/in/products/0830927

| | Climate level | AHT 1.0 S | |
|-----|--|-----------------------------|--|
| | Cycles | 2 | |
| _ | Salt spray test | | |
| | ball spray lest | | |
| | Specification | DIN EN 60068-2-11:2000-02 | |
| | Result | Test passed | |
| | and the second of the second o | | |
| - | ambient conditions | | |
| | Ambient temperature (operation) | -40 °C 120 °C | |
| | Recommended ambient temperature (storage/transport) | 23 °C | |
| | Recommended humidity (storage/transport) | 50 % | |
| | | | |
| Sta | indards and regulations | | |
| | Wipe resistance | DIN EN 61010-1 (VDE 0411-1) | |
| | | | |
| Мо | unting | | |
| | Mounting type | snapped | |



0830927

https://www.phoenixcontact.com/in/products/0830927

Classifications

ECLASS

| | ECLASS-10.0.1 | 27141137 |
|------|---------------|----------|
| | ECLASS-11.0 | 27281101 |
| | ECLASS-12.0 | 27281101 |
| | ECLASS-13.0 | 27281101 |
| ETIM | | |
| | ETIM 8.0 | EC000761 |
| UN | ISPSC | |

UN

| UNSPSC 21.0 | 39131500 |
|---------------|----------|
| 0.10. 00 2.10 | 00.0.000 |



0830927

https://www.phoenixcontact.com/in/products/0830927

Accessories

BM ID-CARTR. BK - Ink cartridge

1044345

https://www.phoenixcontact.com/in/products/1044345



Replacement UV fluid, 23 ml, color: black

BM ID-CARTR. YE - Ink cartridge

1044348

https://www.phoenixcontact.com/in/products/1044348



Replacement UV fluid, 23 ml, color: yellow



0830927

https://www.phoenixcontact.com/in/products/0830927

BM ID-CARTR. CY - Ink cartridge

1044346

https://www.phoenixcontact.com/in/products/1044346



Replacement UV fluid, 23 ml, color: cyan

BM ID-CARTR. MA - Ink cartridge

1044347

https://www.phoenixcontact.com/in/products/1044347



Replacement UV fluid, 23 ml, color: magenta



0830927

https://www.phoenixcontact.com/in/products/0830927

BM ID-CLEANING CARTR. - Cleaning cartridge

1044350

https://www.phoenixcontact.com/in/products/1044350



Replacement cleaning cartridge

BLUEMARK CLED-FLUID-CARTR. - Ink cartridge

5146662

https://www.phoenixcontact.com/in/products/5146662

Cartridge, for replacement, 20 ml UV color, black, including cleaning cartridge





0830927

https://www.phoenixcontact.com/in/products/0830927

BLUEMARK FLUID-CARTRIDGE - Ink cartridge

5147421

https://www.phoenixcontact.com/in/products/5147421

Cartridge, for replacement, 28 ml UV color, black including cleaning cartridge



THERMOMARK-RIBBON 110-TC - Ink ribbon

0801371

https://www.phoenixcontact.com/in/products/0801371



Ink ribbon, for THERMOMARK CARD for printing product groups UCT..., US..., and UM..., roll length: 300 m, width: 110 mm, color: black



0830927

https://www.phoenixcontact.com/in/products/0830927

TMP-RIBBON 110 BK 100 - Ink ribbon cartridge

0803374

https://www.phoenixcontact.com/in/products/0803374

Ink ribbon cartridge, for THERMOMARK PRIME for printing product groups UCT. .., US..., and UM..., roll length: 70 m, width: 110 mm, color: black



BLUEMARK MAG UM-TM - Magazine

0803335

https://www.phoenixcontact.com/in/products/0803335

Magazine for the BLUEMARK printer, for accommodating UM materials



Phoenix Contact 2023 @ - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT (I) Pvt. Ltd. A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420 info@phoenixcontact.co.in