

TeSys F - contactor coil - LX1FF - 220...230 V AC 50Hz - 265...277 V AC 60 Hz

LX1FF220

Discontinued on: 08 October 2021

(!) Discontinued

Main

Range	TeSys
Product or component type	Contactor coil
Device short name	LX1FF
Range compatibility	TeSys (TeSys F) LC1F contactor
Product compatibility	LC1F150 LC1F115
Control circuit type	AC at 50/60 Hz
[Uc] control circuit voltage	220230 V AC 50 Hz 265277 V AC 60 Hz
Inductance of closed circuit	3.44 H
Average resistance	28.1 Ohm at 20 °C
Operating time	2335 ms closing 515 ms opening
Mechanical durability	10 Mcycles
Maximum operating rate	2400 cyc/h 55 °C

Complementary

Coil technology	Without built-in suppressor module	
Control circuit voltage limits	Drop-out: 0.350.55 Uc 50/60 Hz (at 55 °C) Operational: 0.851.1 Uc 50/60 Hz (at 55 °C)	
Inrush power in VA	550 VA 50 Hz cos phi 0.3 (at 20 °C) 660 VA 60 Hz cos phi 0.3 (at 20 °C)	
Hold-in power consumption in VA	45 VA 50 Hz cos phi 0.3 (at 20 °C) 55 VA 60 Hz cos phi 0.3 (at 20 °C)	
Heat dissipation	1216 W at 50/60 Hz	

Environment

Ambient air temperature for operation	-555 °C
Net weight	0.43 kg

Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1	1
Package 1 Height	7 cm
Package 1 Width	8 cm
Package 1 Length	16 cm
Package 1 Weight	494 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty 18 months

Recommended replacement(s)

LX1FF220 is replaced by:



TeSys F - specific contactor coil - 220...230 V AC 40...400 Hz low consumption $\ensuremath{\mathsf{LX9FF220}}$