


Series  
**NSX**

SIZE 8 QUADRAX SOCKET CONTACT

Issue:  
Jan. 06, 2016

Page  
**1/2**



This information is given as an indication. In the continual goal to improve our products, we reserve the right to make any modifications judged necessary.

DIMENSIONS : mm (inch are given for information only)

Estimated weight : 4,20 g

<b>CREATION</b> PEN: M000004358B NOM: VAN DEN B. DATE: April 17, 2001 APPR.: /	Jan. 06, 16	Date code added on the outer body marking	PECAULT B.	Legendre T.
	Jul. 09, 15	Added PIC E50424 cable	PECAULT B.	Legendre T.
	Apr. 13, 15	Added cable CEEW0005-2PF870, page 2 and table 1	Zuniga F.	Ramos D.
	Mar. 09, 15	Added MICT0400005 for ABS1503KL24 cable	Branjonneau V.	Legendre T.
	Sept. 05, 12	Updated way of marking	Legendre T.	Dupuis V.
	June 08, 09	Added Thermax cable.	Macari JP.	Legendre T.
	Sept. 17, 08	Added GSC01-81869-01 cable.	Legendre T.	Brochet L.
	Issue	Revisions	Name	Approved

**MATERIAL:**

- OUTER AND CENTER CONTACTS : COPPER ALLOY
- FERRULE : BRASS PER QQ-B-626
- INSULATOR : PTFE PER ASTM-D-1710 OR EQUIVALENT
- SPACER : THERMOPLASTIC PER ASTM D 5205

**FINISH:**

- ALL METAL PARTS:  
PLATING .00005 INCH OF GOLD PER MIL-G-45204 TYPE I OR II  
GRADE C OR D CLASS 1 OVER NICKEL PER QQ-N-290

**EXTRACTION TOOL:**

- M81969/28.03 (RADIALL: 282 549 001) OR M81969/14-06

TABLE 1	
CABLES	WIRING INSTRUCTION
ABS1503KL24	MICT0400005
ABS1503KD	RP55178
ABS0972	
GSC01-81869-01	
THERMAX T956-4T200	
CEEW0005-2PF870	
PIC E50424	

This document contains proprietary information and such information shall not be disclosed to any third party for any purpose whatsoever or used for manufacturing purposes without prior written agreement from RADIALL. This information is given as an indication. In the continual goal to improve our products, we reserve the right to make any modifications judged necessary.

4112\_9311