

# WT-HT HF 3,6X140 BK - Cable tie



3240783

<https://www.phoenixcontact.com/in/products/3240783>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Cable binders for quick and secure bundling, heat stabilized to 125°C (also up to 145°C for brief periods)

## Commercial Data

Item number	3240783
Packing unit	100 pc
Minimum order quantity	100 pc
Sales Key	BE7
Product Key	BE7131
Catalog Page	Page 617 (C-3-2019)
GTIN	4046356705011
Weight per Piece (including packing)	0.656 g
Weight per Piece (excluding packing)	0.649 g
Customs tariff number	39269097
Country of origin	HR

# WT-HT HF 3,6X140 BK - Cable tie



3240783

<https://www.phoenixcontact.com/in/products/3240783>

## Technical Data

### Product properties

Product type	Cable tie
Type	Internal teeth
Tensile strength GRP	130 N

### Dimensions

Width	3.6 mm
Length	140 mm

### Material specifications

Color	black
Material	PA 6.6
Flammability rating according to UL 94	V2
Components	free from silicone and halogen

### Cable/line

External cable diameter	2 mm ... 35 mm
Tensile strength	130 N

### Environmental and real-life conditions

#### Ambient conditions

Optimum ambient temperature (storage/transport)	23 °C 50 % Polyamide 6.6 has pronounced hygroscopic properties. It absorbs or releases water in accordance with the level of humidity within its environment. Its properties are ideal when the percentage of water is 2 - 3%. The packaging, which is tailored specifically to the product concerned, contains the optimum level of moisture. To ensure that the ideal properties are maintained, the following points should be observed during storage: Keep product stored inside sealed original packaging, carry out any product processing soon after breaking open the packaging, avoid direct sunlight, avoid direct heat.
Ambient temperature (operation)	-40 °C ... 125 °C
Ambient temperature (assembly)	-10 °C ... 60 °C
Short-term temperature	145 °C

### Mounting

Mounting type	Cannot be removed
---------------	-------------------

# WT-HT HF 3,6X140 BK - Cable tie



3240783

<https://www.phoenixcontact.com/in/products/3240783>

## Classifications

### ECLASS

ECLASS-11.0	27140702
ECLASS-13.0	27140702

### ETIM

ETIM 8.0	EC000046
----------	----------

### UNSPSC

UNSPSC 21.0	39121700
-------------	----------

# WT-HT HF 3,6X140 BK - Cable tie



3240783

<https://www.phoenixcontact.com/in/products/3240783>

## Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

# WT-HT HF 3,6X140 BK - Cable tie

3240783

<https://www.phoenixcontact.com/in/products/3240783>



## Accessories

### UNIFOX-CT 4,8 - Cable tie tool

1212475

<https://www.phoenixcontact.com/in/products/1212475>



**Cable binder pliers**, for plastic cable binders with a width of 2.2 - 4.8 mm, for a material thickness of up to 1.6 mm

---

### UNIFOX-CT 4,8P - Cable tie tool

1212609

<https://www.phoenixcontact.com/in/products/1212609>



**Cable binder pliers**, for plastic cable binders with a width of 2.2 - 4.8 mm, for a material thickness of up to 1.6 mm

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.

A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420

[info@phoenixcontact.co.in](mailto:info@phoenixcontact.co.in)