

Product datasheet

Specifications



servo motor BMH - 48 Nm - 4000 rpm - keyed shaft - without brake - IP65/IP67

BMH1902P31A2A

Main

Product or component type	Servo motor
Device short name	BMH
Maximum mechanical speed	4000 rpm
Continuous stall torque	37.4 N.m for LXM32.D72N4 at 24 A, 400 V, three phase 37.4 N.m for LXM32.D72N4 at 24 A, 480 V, three phase 48 N.m for LXM32MD85N4 at 32 A, 400 V, three phase 48 N.m for LXM32MD85N4 at 32 A, 480 V, three phase 48 N.m for LXM32MC10N4 at 40 A, 400 V, three phase 48 N.m for LXM32MC10N4 at 40 A, 480 V, three phase
Peak stall torque	101 N.m for LXM32.D72N4 at 24 A, 400 V, three phase 101 N.m for LXM32.D72N4 at 24 A, 480 V, three phase 115.5 N.m for LXM32MD85N4 at 32 A, 400 V, three phase 115.5 N.m for LXM32MD85N4 at 32 A, 480 V, three phase 130.7 N.m for LXM32MC10N4 at 40 A, 400 V, three phase 130.7 N.m for LXM32MC10N4 at 40 A, 480 V, three phase
Nominal output power	5900 W for LXM32.D72N4 at 24 A, 400 V, three phase 5900 W for LXM32.D72N4 at 24 A, 480 V, three phase 6070 W for LXM32MD85N4 at 32 A, 400 V, three phase 6070 W for LXM32MD85N4 at 32 A, 480 V, three phase 6070 W for LXM32MC10N4 at 40 A, 400 V, three phase 6070 W for LXM32MC10N4 at 40 A, 480 V, three phase
Nominal torque	22.3 N.m for LXM32.D72N4 at 24 A, 400 V, three phase 22.3 N.m for LXM32.D72N4 at 24 A, 480 V, three phase 29 N.m for LXM32MD85N4 at 32 A, 400 V, three phase 29 N.m for LXM32MD85N4 at 32 A, 480 V, three phase 29 N.m for LXM32MC10N4 at 40 A, 400 V, three phase 29 N.m for LXM32MC10N4 at 40 A, 480 V, three phase
Nominal speed	2000 rpm for LXM32MC10N4 at 40 A, 400 V, three phase 2000 rpm for LXM32MC10N4 at 40 A, 480 V, three phase 2500 rpm for LXM32.D72N4 at 24 A, 400 V, three phase 2500 rpm for LXM32.D72N4 at 24 A, 480 V, three phase 2000 rpm for LXM32MD85N4 at 32 A, 400 V, three phase 2000 rpm for LXM32MD85N4 at 32 A, 480 V, three phase
Product compatibility	LXM32.D72N4 at 400...480 V three phase
Shaft end	Keyed
IP degree of protection	IP65 standard IP67 with IP67 kit
Speed feedback resolution	131072 points/turn
Holding brake	Without
Mounting support	International standard flange
Electrical connection	Rotatable right-angled connectors

Complementary

Range compatibility	Lexium 32
[Us] rated supply voltage	480 V
Network number of phases	Three phase
Continuous stall current	30.8 A
Continuous power	6.1 W
Maximum current Irms	72 A for LXM32.D72N4
Maximum permanent current	114 A
Second shaft	Without second shaft end
Shaft diameter	38 mm
Shaft length	80 mm
Key width	70 mm
Feedback type	Single turn SinCos Hiperface
Motor flange size	190 mm
Number of motor stacks	2
Torque constant	1.56 N.m/A at 120 °C
Back emf constant	108.3 V/krpm at 120 °C
Number of motor poles	10
Rotor inertia	130.1 kg.cm ²
Stator resistance	0.15 Ohm at 20 °C
Stator inductance	3.86 mH at 20 °C
Stator electrical time constant	25.7 ms at 20 °C
Maximum radial force Fr	4200 N at 1000 rpm
Maximum axial force Fa	0.2 x Fr
Type of cooling	Natural convection
Length	250 mm
Centring collar diameter	180 mm
Centring collar depth	4 mm
Number of mounting holes	4
Mounting holes diameter	14 mm
Circle diameter of the mounting holes	215 mm
Net weight	31 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	30.0 cm
Package 1 Width	40.0 cm
Package 1 Length	79.5 cm
Package 1 Weight	31.5 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)