

https://www.phoenixcontact.com/in/products/0201155



Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

Insertion bridge, pitch: 6.2 mm, number of positions: 2, color: gray



Commercial Data

Item number	0201155
Packing unit	100 pc
Minimum order quantity	100 pc
Sales Key	BE1
Product Key	BE1Z2X
Catalog Page	Page 467 (C-1-2019)
GTIN	4017918098278
Weight per Piece (including packing)	1.129 g
Weight per Piece (excluding packing)	1.129 g
Customs tariff number	85366990
Country of origin	CN



https://www.phoenixcontact.com/in/products/0201155



Technical Data

Product properties

Product type	Insertion bridge
Number of positions	2
Pitch	6.2 mm

Dimensions

Dir. I	
Pitch	6.2 mm

Material specifications

Color	gray
Material	CuZn (nickel-plated)
Flammability rating according to UL 94	V2
Insulating material	PA

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-60 °C 105 °C
Ambient temperature (storage/transport)	-25 °C 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C 70 °C
Ambient temperature (actuation)	-5 °C 70 °C
Permissible humidity (storage/transport)	30 % 70 %

Mounting

Mounting type	Screw mounting



https://www.phoenixcontact.com/in/products/0201155



Classifications

ECLASS

	ECLASS-11.0	27141140
	ECLASS-12.0	27141140
	ECLASS-13.0	27250303
ETIM		
	ETIM 8.0	EC000489

UNSPSC

0201155

https://www.phoenixcontact.com/in/products/0201155



Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2023 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT (I) Pvt. Ltd. A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420 info@phoenixcontact.co.in