



encoder interface card with RS422 compatible differential outpts - 5 V DC

VW3A3401

Product availability: Stock - Normally stocked in distribution facility

Price*: 85.00 USD

Main

mani	
Range of Product	Altivar
Product or Component Type	Encoder interface card
Range Compatibility	Altivar Lift Altivar 61 Altivar 71Q Altivar 71 Altivar 61Q
Discrete output type	Differential
Communication port protocol	RS422
[Us] rated supply voltage	5 V DC 55.5 V)
Number of pulses per revolution	10000 ATV71H383 5000 all ATV61 drives 5000 ATV71HM3 5000 ATV71HM3X 5000 ATV71HN4

Complementary

Maximum supply current	0.2 A
Protection Type	Short-circuit protection Overload protection
Maximum cable distance between devices	164.04 ft (50 m)
Maximum operating frequency	300 kHz
Input signal	A B compliment of A compliment of B
Input impedance	440 Ohm
Electrical connection	Terminal 0.2 mm² AWG 24) <82.02 ft (25 m), encoder, 100 mA 4.5 V Terminal 0.5 mm² AWG 20) <82.02 ft (25 m), encoder, 200 mA 4.5 V Terminal 0.5 mm² AWG 20) <164.04 ft (50 m), encoder, 100 mA 4.5 V Terminal 0.75 mm² AWG 18) <164.04 ft (50 m), encoder, 200 mA 4.5 V
Net Weight	0.44 lb(US) (0.2 kg)

Ordering and shipping details

Category	22135-ATV61-71 ACCESSORIES
Discount Schedule	CP4C

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

GTIN	3389118067202
Returnability	No
Country of origin	ID
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.95 in (7.5 cm)
Package 1 Width	6.69 in (17.0 cm)
Package 1 Length	9.06 in (23.0 cm)
Package 1 Weight	5.33 oz (151.0 g)
Unit Type of Package 2	S03
Number of Units in Package 2	7
Package 2 Height	11.81 in (30.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	3.26 lb(US) (1.479 kg)
Offer Sustainability	
Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty 18 months

Recommended replacement(s)