



## Ethercat 2 x RJ45 communication module

VW3A3601

Main

Range of product Altivar

Product or component type Communication module

Complementary

Range compatibility Altivar Process Modular

Altivar Machine ATV340 except Sercos drives

Altivar Machine ATV320 Altivar Process ATV900

Altivar 32 Lexium 32

Lexium 32 **Product compatibility** 

FtherCAT **Communication port protocol** 

2 connectors RJ45 **Electrical connection** 

Transmission rate 100 Mbps

Maximum cable distance 100 m for 100 Mbps

Addressing Logical addressing Node addressing

Position addressing

**Communication service** PDO and SDO support

Drive profile CiA 402 velocity mode conforming to IEC 61800-7-201 (CiA 402)

CANopen over EtherCAT (CoE)

Display type 1 LED for input status

1 LED for RUN

1 LED for error

60.0 g

1 LED for output status

**Environment** 

between devices

**Standards** IEC 61800-7-201 (CiA 402)

**Packing Units** 

Package 1 Weight

PCE Unit Type of Package 1 Number of Units in Package 1 6.3 cm Package 1 Height Package 1 Width 4.5 cm 9.0 cm Package 1 Length

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Unit Type of Package 2	S03
Number of Units in Package 2	100
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	6.58 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
PVC free	Yes
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

## **Contractual warranty**

Warranty 18 months

Recommended replacement(s)