



TeSys VARIO - additional neutral block - 40 A - for V02...V2

VZ11

Main

Range	TeSys
Device short name	VZ
Product or component type	Additional neutral block
Performance level	High performance
Poles description	1N
Contacts type and composition	1 NO
Contact operation	Early make, late break
Product compatibility	V1 V2 V02 V0 V01
Range compatibility	TeSys (TeSys VARIO) switch disconnector
Network type	AC DC
Network frequency	50/60 Hz

Complementary

Mounting location	Right Left
[Ue] rated operational voltage	690 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	6 kV
[Ith] conventional free air thermal current	40 A
Mechanical durability	100000 cycles
Electrical durability	30000 cycles DC-15 100000 cycles AC-21
Connections - terminals	Screw clamp terminals6 mm² - flexible - with cable end Screw clamp terminals10 mm² - solid
Tightening torque	2.1 N.m - on screw clamp terminals
Height	74 mm
Width	16 mm
Depth	35 mm

	0.051
Net weight	0.05 kg
Environment	
Standards	IEC 60947-3
Product certifications	GL CSA UL UKCA
Protective treatment	TC
IP degree of protection	IP20 conforming to IEC 60529
Mechanical robustness	Vibrations 10150 Hz (1 gn) conforming to IEC 60068-2-6 Shocks 11 ms (15 gn) conforming to IEC 60068-2-27
Ambient air temperature for operation	-2050 °C
Fire resistance	960 °C conforming to IEC 60695-2-1
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.7 cm
Package 1 Width	5.5 cm
Package 1 Length	9.0 cm
Package 1 Weight	48.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	69
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	3.582 kg
Offer Sustainability	
Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
Halogen content performance	Halogen free product
Contractual warranty	
Warranty	18 months

Recommended replacement(s)

Life Is On Schneider