


**RIGHT ANGLE JACK RECEPTACLE FOR PCB
SOLDER LEGS**

R124.680.123
SERIES SMA-COM



| | | |
|---------------------------------|-----------------|--------------------------|
| NOMINAL IMPEDANCE | 50 | Ω |
| FREQUENCY RANGE | 0-18 | GHz |
| TEMPERATURE RATING | -65/+165 | $^{\circ}$ C |
| V.S.W.R | 1.30* | + x F(GHz)Maxi |
| RF INSERTION LOSS | 0.07 | \sqrt{F} (GHz) dB Maxi |
| VOLTAGE RATING | 500 | Veff Maxi |
| DIELECTRIC WITHSTANDING VOLTAGE | 1000 | Veff Mini |
| INSULATION RESISTANCE | 5000 | M Ω Mini |
| HERMETIC SEAL | NA | Atm.cm ³ /s |
| LEAKAGE (pressurized only) | NA | |
| MECHANICAL DURABILITY | 100 | Cycles |
| WEIGHT | 2.98 | gr |
| SPECIFICATION | | |

| | |
|----------------------------|--------------------------------|
| CABLES : | |
| OTHERS CHARACTERISTICS | * VSWR maxi up to 6 GHz |
| CABLE RETENTION | NA N Mini |
| CENTER CONTACT RETENTION | |
| Axial force - mating end | 27 N Mini |
| Axial force - opposite end | 27 N Mini |
| Torque | NA cm.N Mini |
| RECOMMENDED TORQUES | |
| Mating | NA cm.N |
| Panel nut | NA cm.N |
| Clamp nut | NA cm.N |

| | | | |
|------------------|------------------|--------------------------|---------------------------------------|
| CONNECTOR PARTS: | MATERIALS | FINISH | (all values are given in micrometers) |
| BODY | BRASS | GOLD 0.2 OVER NICKEL 2 | |
| OUTER CONTACT | | | |
| CENTER CONTACT | BERYLLIUM COPPER | GOLD 1.3 OVER COPPER 2.5 | |
| INSULATOR | PTFE | - | |
| GASKET | | - | |
| OTHERS PIECES | BRASS | GOLD 0.2 OVER NICKEL 2 | |

| | | |
|----------------|-------------------|------------------|
| ISSUE | CREATION DATE | FILE PART-NUMBER |
| 9938C01 | 15/06/1993 | EPC 97-03 |



RADIALL[®]

TRIQUES E.

The information given here is subject to change without notice.
Design changes may be in order to improve the product .

Connect to the future