

KGS-MSTB 2,5/20 - Cable housing

1805615

<https://www.phoenixcontact.com/in/products/1805615>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Cable housing, pitch: 0 mm, number of positions: 20, dimension a: 100 mm, color: green

Commercial Data

Item number	1805615
Packing unit	10 pc
Minimum order quantity	10 pc
Sales Key	AAH
Product Key	AAHZDD
Catalog Page	Page 194 (CC-2005)
GTIN	4017918046620
Weight per Piece (including packing)	28.98 g
Weight per Piece (excluding packing)	28.75 g
Customs tariff number	85389099
Country of origin	PL

KGS-MSTB 2,5/20 - Cable housing



1805615

<https://www.phoenixcontact.com/in/products/1805615>

Technical Data

Product properties

Product type	Cable housing
Product family	KGS-MSTB 2,5
Number of positions	20
Pitch	0.00 mm

Material specifications

Color	green
Flammability rating according to UL 94	HB
Insulating material group	I
Insulating material	ABS

Dimensions

Width	19.8 mm
Height	55.8 mm
Pitch	0.00 mm

KGS-MSTB 2,5/20 - Cable housing



1805615

<https://www.phoenixcontact.com/in/products/1805615>

Approvals



EAC

Approval ID: B.01687

KGS-MSTB 2,5/20 - Cable housing



1805615

<https://www.phoenixcontact.com/in/products/1805615>

Classifications

ECLASS

ECLASS-11.0	27460402
ECLASS-11.0	27460402
ECLASS-11.0	27460402

ETIM

ETIM 8.0	EC002943
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

KGS-MSTB 2,5/20 - Cable housing



1805615

<https://www.phoenixcontact.com/in/products/1805615>

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e No hazardous substances above threshold values
------------	---

KGS-MSTB 2,5/20 - Cable housing

1805615

<https://www.phoenixcontact.com/in/products/1805615>




Accessories

KGS-MSTB 2,5/ DST - Cable housing

1784914

<https://www.phoenixcontact.com/in/products/1784914>



Transparent label carrier, can be marked with marker strips SBS 2.5/7.5

SBS 2,5/7,5 - Marker for terminal blocks

1007604

<https://www.phoenixcontact.com/in/products/1007604>



Marker for terminal blocks, Card, white, unlabeled, can be labeled with: Marker pen, perforated, mounting type: snap in, snap into flat marker groove, for terminal block width: 7.5 mm, lettering field size: 15 x 7.5 mm, Number of individual labels: 10

KGS-MSTB 2,5/20 - Cable housing

1805615

<https://www.phoenixcontact.com/in/products/1805615>

KD-KGS-MSTB - Accessories

1804658

<https://www.phoenixcontact.com/in/products/1804658>




Molded cable strain relief, suitable for KGS-... cable housings, prevents the cable from being bent

MSTB 2,5/20-ST - PCB connector

1754805

<https://www.phoenixcontact.com/in/products/1754805>



PCB connector, nominal cross section: 2.5 mm², color: green, nominal current: 12 A, rated voltage (III/2): 320 V, contact surface: Tin, type of contact: Socket, number of potentials: 20, number of rows: 1, number of positions: 20, number of connections: 20, product range: MSTB 2,5/..-ST, pitch: 5 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: 0 °, locking clip: - Locking clip, plug-in system: COMBICON MSTB 2,5, locking: without, mounting: without, type of packaging: packed in cardboard

KGS-MSTB 2,5/20 - Cable housing

1805615

<https://www.phoenixcontact.com/in/products/1805615>

MSTB 2,5/20-ST-5,08 - PCB connector

1757190

<https://www.phoenixcontact.com/in/products/1757190>



PCB connector, nominal cross section: 2.5 mm², color: green, nominal current: 12 A, rated voltage (III/2): 320 V, contact surface: Tin, type of contact: Socket, number of potentials: 20, number of rows: 1, number of positions: 20, number of connections: 20, product range: MSTB 2,5/...-ST, pitch: 5.08 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: 0 °, locking clip: - Locking clip, plug-in system: COMBICON MSTB 2,5, locking: without, mounting: without, type of packaging: packed in cardboard

MSTB 2,5/20-STF - PCB connector

1787018

<https://www.phoenixcontact.com/in/products/1787018>



PCB connector, nominal cross section: 2.5 mm², color: green, nominal current: 12 A, rated voltage (III/2): 320 V, contact surface: Tin, type of contact: Socket, number of potentials: 20, number of rows: 1, number of positions: 20, number of connections: 20, product range: MSTB 2,5/...-STF, pitch: 5 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: 0 °, locking clip: - without locking clip, plug-in system: COMBICON MSTB 2,5, locking: Screw locking, mounting: Screw flange, type of packaging: packed in cardboard

KGS-MSTB 2,5/20 - Cable housing

1805615

<https://www.phoenixcontact.com/in/products/1805615>

MSTB 2,5/20-STF-5,08 - PCB connector

1778166

<https://www.phoenixcontact.com/in/products/1778166>




PCB connector, nominal cross section: 2.5 mm², color: green, nominal current: 12 A, rated voltage (III/2): 320 V, contact surface: Tin, type of contact: Socket, number of potentials: 20, number of rows: 1, number of positions: 20, number of connections: 20, product range: MSTB 2,5/...-STF, pitch: 5.08 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: 0 °, locking clip: - without locking clip, plug-in system: COMBICON MSTB 2,5, locking: Screw locking, mounting: Screw flange, type of packaging: packed in cardboard

IC 2,5/20-ST-5,08 - PCB connector

1786352

<https://www.phoenixcontact.com/in/products/1786352>



PCB connector, nominal cross section: 2.5 mm², color: green, nominal current: 12 A, rated voltage (III/2): 320 V, contact surface: Tin, type of contact: Pin, number of potentials: 20, number of rows: 1, number of positions: 20, number of connections: 20, product range: IC 2,5/...-ST, pitch: 5.08 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: 0 °, locking clip: - without locking clip, plug-in system: COMBICON MSTB 2,5, locking: without, mounting: without, type of packaging: packed in cardboard

KGS-MSTB 2,5/20 - Cable housing




1805615

<https://www.phoenixcontact.com/in/products/1805615>

IC 2,5/20-STF-5,08 - PCB connector

1825491

<https://www.phoenixcontact.com/in/products/1825491>



PCB connector, nominal cross section: 2.5 mm², color: green, nominal current: 12 A, rated voltage (III/2): 320 V, contact surface: Tin, type of contact: Pin, number of potentials: 20, number of rows: 1, number of positions: 20, number of connections: 20, product range: IC 2,5/...-STF, pitch: 5.08 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: 0 °, locking clip: - without locking clip, plug-in system: COMBICON MSTB 2,5, locking: Screw locking, mounting: Screw flange, type of packaging: packed in cardboard

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.

A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420

info@phoenixcontact.co.in