#### Main

Main	
Range	TeSys
Product name	TeSys LC1D.K TeSys Deca
Product or component type	Capacitor duty contactor
Device short name	LC1DLK
Contactor application	Power factor correction
Poles description	3P
Power pole contact composition	3 NO
[Ue] rated operational voltage	Power circuit: <= 690 V AC 50/60 Hz
Reactive power rating	10 kvar at 220…240 V AC 50/60 Hz 55 °C 20 kvar at 400…440 V AC 50/60 Hz 55 °C 30 kvar at 660…690 V AC 50/60 Hz 55 °C
Control circuit type	AC at 50/60 Hz
[Uc] control circuit voltage	220 V AC 50/60 Hz
Auxiliary contact composition	1 NO + 1 NC
Mounting support	Plate Rail
Standards	IEC 60831 IEC 60070 VDE 0560 NF C 54-100
Product certifications	CSA UL UKCA
Connections - terminals	Power circuit: connector 1 4 mm² - cable stiffness: flexible with cable end Power circuit: connector 2 6 mm² - cable stiffness: solid with cable end Power circuit: connector 1 10 mm² - cable stiffness: solid with cable end Power circuit: connector 2 4 mm² - cable stiffness: flexible with cable end
Tightening torque	Power circuit: 1.9 N.m - on connector

### Complementary

Auxiliary contacts type type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1 type mirror contact 1 NC conforming to IEC 60947-4-1

#### **Environment**

IP degree of protection IP2X conforming to IEC 60529

Protective treatment	TH conforming to IEC 60068-2-30
Ambient air temperature for operation	-560 °C
Ambient air temperature for storage	-6080 °C
Operating altitude	03000 m
Height	84 mm
Width	56 mm
Depth	117 mm
Net weight	0.6 kg

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.4 cm
Package 1 Width	20.8 cm
Package 1 Length	15.2 cm
Package 1 Weight	666.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	10
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	7.373 kg
Unit Type of Package 3	P06
Number of Units in Package 3	80
Package 3 Height	77.0 cm
Package 3 Width	80.0 cm
Package 3 Length	60.0 cm
Package 3 Weight	67.484 kg

# Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

#### **Contractual warranty**

Warranty

18 months

# Recommended replacement(s)

LC1DLK11M7 is replaced by:

1x



TeSys LC1D.K capacitor duty contactor - 3P - 20 kVAR - 415 V - 220 V AC coil LC1DLKM7