

https://www.phoenixcontact.com/in/products/3209824



Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Flange cover, length: 35.8 mm, width: 4.5 mm, height: 24.7 mm, color: gray

### **Product Description**

Flange cover, can be snapped onto SP-H 2,5/... and PP-H 2,5/... connectors

### Your advantages

- For reliable screw connection between the plug and screw flange
- The flange covers can be snapped onto the plug housing later on

### **Commercial Data**

Item number	3209824
Packing unit	50 pc
Minimum order quantity	50 pc
Sales Key	BE2
Product Key	BE2Z1X
Catalog Page	Page 372 (C-1-2019)
GTIN	4046356367035
Weight per Piece (including packing)	1.435 g
Weight per Piece (excluding packing)	1.43 g
Customs tariff number	85389099
Country of origin	PL



https://www.phoenixcontact.com/in/products/3209824



### **Technical Data**

### Product properties

Product type	End cover

### Environmental and real-life conditions

#### Ambient conditions

Ambient temperature (operation)	-60 °C 105 °C (max. short-term operating temperature RTI Elec.)
Ambient temperature (storage/transport)	-25 °C 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C 70 °C
Ambient temperature (actuation)	-5 °C 70 °C
Permissible humidity (storage/transport)	30 % 70 %

### Material specifications

Color	gray
Flammability rating according to UL 94	V0
Insulating material	PA
Static insulating material application in cold	-60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	125 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Calorimetric heat release NFPA 130 (ASTM E 1354)	27,5 MJ/kg
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

#### **Dimensions**

Width	4.5 mm
Height	24.7 mm
Length	35.8 mm



https://www.phoenixcontact.com/in/products/3209824



### Classifications

### **ECLASS**

	ECLASS-10.0.1	27141133
	ECLASS-11.0	27141133
	ECLASS-12.0	27141133
	ECLASS-13.0	27250301
ETIM		
	ETIM 8.0	EC000886

### **UNSPSC**

UNSPSC 21.0 3	39121400
---------------	----------



https://www.phoenixcontact.com/in/products/3209824



### **Environmental Product Compliance**

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values



https://www.phoenixcontact.com/in/products/3209824



#### Accessories

ST 2,5/1P-F - Screw flange

3209837

https://www.phoenixcontact.com/in/products/3209837



Screw flange, for screwing COMBI plugs, with the same structure and pitch as the relevant COMBI terminal blocks

### ST 2,5/2P-F - Screw flange

3061198

https://www.phoenixcontact.com/in/products/3061198



Screw flange, for screwing COMBI plugs, with the same structure and pitch as the relevant COMBI terminal blocks



https://www.phoenixcontact.com/in/products/3209824



### ST 2,5-TWIN/1P-F - Screw flange

3209840

https://www.phoenixcontact.com/in/products/3209840



Screw flange, for screwing COMBI plugs, with the same structure and pitch as the relevant COMBI terminal blocks

### ST 2,5-QUATTRO/2P-F - Screw flange

3209853

https://www.phoenixcontact.com/in/products/3209853

Screw flange, for screwing COMBI plugs, with the same structure and pitch as the relevant COMBI terminal blocks





https://www.phoenixcontact.com/in/products/3209824



### ST 2,5-QUATTRO/4P-F - Screw flange

3061208

https://www.phoenixcontact.com/in/products/3061208

Screw flange, for screwing COMBI plugs, with the same structure and pitch as the relevant COMBI terminal blocks



### QTC 1,5/1P-F - Screw flange

3061211

https://www.phoenixcontact.com/in/products/3061211



Screw flange, for screwing COMBI plugs, with the same structure and pitch as the relevant COMBI terminal blocks



https://www.phoenixcontact.com/in/products/3209824



### QTTCB 1,5/2P-F - Screw flange

3061185

https://www.phoenixcontact.com/in/products/3061185

Screw flange, for screwing COMBI plugs, with the same structure and pitch as the relevant COMBI terminal blocks



Phoenix Contact 2023 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT (I) Pvt. Ltd. A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420 info@phoenixcontact.co.in