

18.0 V CORDLESS HYDRAULIC CUTTING TOOL B-TC650

Overhead line application

□

Cordless Alliance System



compliant

Next generation of 18.0 V cordless hydraulic cutting tool specifically designed to cut Copper, Aluminium and telecommunication cable having a max overall diameter of 65 mm. The blades are manufactured from high strength special Steel, heat treated to ensure a long service life.

New Li-Ion 18 V 4 Ah batteries offer a higher capacity than 14.4 V 3 Ah, while greater cutting speed and cutting force result from a revitalised hydraulic system with double speed action. The battery is equipped with LED indicators to show the remaining battery life at any time by pressing the adjacent button.

The head can rotate through 335 degrees, to enable the operator to work in the most comfortable position, and can easily be opened to allow cutting of running cables.

Fitted with a maximum hydraulic pressure valve.

Designed with improved balance, B-TC650 is easily manageable during the cutting process and, by the use of bi-component plastics, has a shell with high resistance to wear and damage.

Rubber grip inserts, low noise and minimal vibration aid operator comfort while additional convenience and safety are provided by LED lighting of the working area.

Operating temperature: -15 to +50 ° C

The tool is supplied as:

- *Basic tool with battery and shoulder strap*
- *Spare battery*
- *Battery charger*
- *Plastic carrying case*

Certificates

□ Directive 2006/42/EC

18.0 V CORDLESS HYDRAULIC CUTTING TOOL B-TC650

Technical characteristics

Properties

Type of action	Cutting
Maximum cutting diameter	65 mm
Nominal pressure	700 bar
Impulse voltage	18 V
Battery current	5.2 Ah
Height	429 mm
Width	415 mm
Length	83 mm
Weight	6.4 kg

□□

18.0 V CORDLESS HYDRAULIC CUTTING TOOL B-TC650

In the same kit

Accessories

Shoulder strap 6000354

USB cable 6006309

Battery charger ASC30-36 - ASC30-36-AUS/NZ

Batteries CB - Li-Ion high power battery CB1852L

Battery charger ASC55 - ASC55-EU

Storage

- Plastic case VAL P40