

BENCH PRESS ELB-3

for polycarbonate insulated chain connectors

Electro-pneumatic, production bench press, controlled by a foot operated pedal. Producing a consistent and reliable crimped connection. Interchangeable application heads available to suit the complete range of polycarbonate insulated connectors.



BENCH PRESS ELB-3

Technical characteristics

PROPERTIES

| | |
|---------------------|---------|
| Height | 620 mm |
| Width | 250 mm |
| Length | 180 mm |
| Weight | 41 kg |
| Motor voltage | 220 V |
| Motor frequency | 50 Hz |
| RPM (to the minute) | 2,800 |
| Motor power | 0.55 kW |
| Motor power | 0.75 HP |
| Type of action | Crimp |



BENCH PRESS ELB-3

Products used together

Connectors

INSULATED CHAIN TERMINALS CP

| | | |
|------------|-------------|-------------|
| CBP-F405 | CBP-F408 | CBP-F408P |
| CBP-F608 | CBP-F608P | CBP-M3 |
| CBP-M3.5 | CBP-M3.5/1 | CBP-M4 |
| CBP-M5 | CBP-M6 | CBP-M6/1 |
| CBP-M608 | CBP-M7 | CBP-M8 |
| CBP-P10 | CBP-P12 | CBP-P8 |
| CBP-PP12 | CBP-PP12/25 | CBP-PPL30 |
| CBP-U3 | CBP-U3.5 | CBP-U4 |
| CBP-U4/1 | CBP-U4/2 | CBP-U4/3L |
| CBP-U5 | CBP-U6 | CGP-F608 |
| CGP-F608P | CGP-M3 | CGP-M3.5 |
| CGP-M4 | CGP-M5 | CGP-M6 |
| CGP-M6/1 | CGP-M608 | CGP-M7 |
| CGP-M8 | CGP-M8/1 | CGP-P10 |
| CGP-P12 | CGP-P14 | CGP-PP12 |
| CGP-PP17 | CGP-U3.5 | CGP-U4 |
| CGP-U5 | CGP-U6 | CRP-F305 |
| CRP-F308 | CRP-F405 | CRP-F405P |
| CRP-F408 | CRP-F408P | CRP-F608 |
| CRP-F608P | CRP-M3 | CRP-M3.5 |
| CRP-M3.5/1 | CRP-M4 | CRP-M4/3 |
| CRP-M5 | CRP-M6 | CRP-M6/1 |
| CRP-M608 | CRP-M7 | CRP-M8 |
| CRP-P10 | CRP-P12 | CRP-P8 |
| CRP-PP12 | CRP-PP12/1 | CRP-PP12/23 |
| CRP-PP14 | CRP-PPL30 | CRP-U3 |
| CRP-U3.5 | CRP-U3.5/2 | CRP-U4 |
| CRP-U4/1 | CRP-U4/2 | CRP-U5 |
| CRP-U6 | CRP-U6/1 | CRP-U8 |

POLYPROPYLENE INSULATED END SLEEVES PK

| | | |
|---------|----------|----------|
| CPKD108 | CPKD1508 | CPKD2508 |
| CPKD508 | CPKD7508 | |

On request

Nest

Interchangeable applicator heads A-3

BA-3

GA-3

KE1A-3

KE2.5A-3

RA-3